

Vitex Kitchen & Bath



Protective paint against mould and fungi

Emulsion paint suitable for the painting of interior surfaces in areas with high moisture and vapour condensation such as kitchens, bathrooms, ceilings and basements. Kitchen & Bath, due to its special formulation prevents effectively the growth of mould and fungi in the film of paint. It provides great hiding power, high spreading rate and superior whiteness. It has very good leveling properties and produces a smooth, flat surface. It can be applied to properly prepared surfaces of any material.

- Prevents the growth of mould and fungi
- For areas with high moisture and vapour condensation

COLOURS

Available in white and a wide range of shades through Vitex's Colorfull Tinting System.

PACKAGING

White	750 mL	3 L	9 L
Bases	1 L	3 L	

SPREADING RATE

11 - 13 m²/L per coat on properly prepared surfaces.

VOC (Volatile Organic Compounds) CONTENT

EU maximum VOC content limit values (Directive 2004/42/CE) for this product (category **A/a** "Interior matt walls and ceilings (Gloss<25@60°)", Type **WB**): **30 g/L**. This product contains maximum **29 g/L** VOCs (ready for use).

SURFACE PREPARATION

Surfaces should be smooth, clean and dry, free from grease, dust, loose or flaking paint.

To fill any cracks or holes use Acrylic Putty or Visto.

Surfaces with mould, fungi and stains must be first cleaned with Kitchen & Bath Cleaner.

Surfaces previously covered with water paints or distempers (lime wash or ceiling white) should be primed with Acrylan Unco Eco or Durovit.

New surfaces made of plaster, concrete, cement, plasterboard, etc. should be first primed with 100% Acrylic Primer or Acrylan Unco Eco or Blanco Eco.

Surfaces stained from smoke, graffiti, coffee or any other kind of stain should first be primed with Blanco Eco or Vitosin.



APPLICATION

Stir well before use. Apply two coats by roller, brush or airless spray gun diluted up to 10% with water. Do not apply at temperature below 5°C, above 35°C and / or relative humidity above 80%.

It is touch-dry after 30-60 minutes and can be recoated after 3-4 hours. Drying time depends on weather conditions (humidity and temperature).

Allow at least 3 weeks before cleaning and washing newly painted surfaces with Vitex Kitchen & Bath. Wash gently with water using a soft sponge. In case of bad stains, use a mild colourless detergent or soapy water.

Tools must be cleaned immediately after use with water and if needed with soapy water or a detergent.

TECHNICAL CHARACTERISTICS

Viscosity	110 ± 10 KU (ASTM D 562, 25°C)
Density	1,59 ± 0,02 Kg/L (ISO 2811) for white
Gloss	< 5 units @ 60° (ISO 2813)

STORAGE

Containers must be kept closed in a cool, dry, well ventilated area protected from direct sunlight at temperatures between 5°C - 38°C.

SAFETY ADVICE

Read label before use. For further instructions - precautions see Material Safety Data Sheet.



T.Θ. 139 Ημερος Τόπος, Ασπρόπυργος Τ.Κ. 193 00
P.O. Box 139 Imeros Topos, Aspropyrgos GR 193 00
T. + 30 210 5589 500, F. + 30 210 4835 007, www.vitex.gr