

Light Acrylic Putty

Acrylic Base Putty



White, ready to use acrylic ultra light with high opacity putty for filling and repairing cracks and holes in walls, plasterboards and ceilings for interior application. It is easy to use, does not shrink, is fast drying, sandable and paintable with any paint.

- For filling large and small holes and cracks
- Does not shrink, it dries fast and is easy sandable

COLOURS

Available in white.

PACKAGING

White	750 mL
-------	--------

VOC (Volatile Organic Compounds) CONTENT

EU maximum VOC content limit values (Directive 2004/42/CE) for this product (category **A/g** "Primers", Type **WB**): **30 g/L**. This product contains maximum **10 g/L** VOCs (ready for use product).

SURFACE PREPARATION

Surfaces must be clean, dry and smooth, free from dust, grease, loose material.

APPLICATION

Apply the product using a spatula/knife without dilution, finish and smoothen with a wet spatula. After 1-2 hours, the product is rubbed with sandpaper and surface is paintable with any emulsion or acrylic water-based or solvent-based coating of Vitex.

Do not apply at temperature below 5°C, above 35°C and/or relative humidity above 80%.

It is touch dry in 5-15 minutes, depending from absorption of the surface. Drying time depends on weather conditions (humidity and temperature).

Tools must be cleaned immediately after use with water and if needed with soapy water or a detergent.



TECHNICAL CHARACTERISTICS

Density	0,57 ± 0,02 Kg/L (ISO 2811)
---------	-----------------------------

STORAGE

Containers must be kept closed in a cool, dry, well ventilated area protected from direct sunlight at temperatures between 5°C - 38°C.

SAFETY ADVICE

Read label before use. For further instructions - precautions see Material Safety Data Sheet.



T.Θ. 139 Ημερος Τόπος, Ασπρόπυργος Τ.Κ. 193 00
P.O. Box 139 Imeros Topos, Aspropyrgos GR 193 00
T. + 30 210 5589 500, F. + 30 210 4835 007, www.vitex.gr