

ATHENS: V. MOIRA, INDUSTRIAL AREA MANDRA, 19600, ATHENS, GREECE, TEL.:+30 210 5557579, FAX: +30 210 5558482

THESSALONIKI: 10th km N.R THESSALONIKIS-POLIGIROU, 57001, THERMI THESSALONIKI, GREECE, TEL.:+30 2310 467275, FAX: 2310 463442

N-Thermon[®] Glue

Description of the product Special glue for adhering **N-Thermon[®]** insulation boards on surfaces such as walls and ceilings.

Properties

- -Very strong adhesion on masonry substrates
- -It is not affected by adverse weather conditions and maintains its strength for temperatures up to -42 oC
- -Suitable for polystyrene sheets
- -Suitable for interior and exterior use

Technical characteristics

| | |
|--------------------------------------|-----------------------------|
| Appearance | high viscous paste |
| Density (ISO 8962, DIN 51757) | 1,43-1,45 g/cm ³ |
| pH (ISO 1148, DIN 53785) | 8-9 |
| Consumption | 500-700gr/m ² |

Instruction for use

Surface preparation: The surface should be dry and free from dust, dirt, greasy and oily substances as well as remnants of old glue. Clean the substrate with a fungicide liquid.

Apply **N-Thermon[®] Glue** on the surface with a brush or suitable spatula in layer of uniform thickness. Then press **N-Thermon[®]** board on the glued surface. **N-Thermon[®] Glue** is suitable also for adhering woven fiberglass fabric **Gavatex** on **N-Thermon[®]** boards or other masonry substrate.

Packing 15 kg, 5kg and 1kg plastic containers

Notes The glue obtains its full endurance 48hours after application at 25 °C. Use water to clean tools after application. Minimum application temperature: 5 °C.

Stain Removal Use water when the stain is still fresh and damp. In case of hardened stains, use mechanical means.

Storage Stability 24 months when kept sealed in its original container in dry and covered place

Safety precautions Keep out of the reach of children - Avoid contact with skin - Wear suitable gloves - Do not empty into drains.