



DESCRIPTION

MINOS CONTACT CLEANER is highly penetrating, fast drying cleaner suitable for cleaning and degreasing electrical contacts. Loosens dirt, grease and impurities. Prevents and removes faults caused by moisture. It is electrically neutral and totally residue-free. Frequent use guarantees the optimum operation of electrical contacts and installations.

ADVANTAGES

- Excellent penetration
- Strong cleaning action
- High dissolving properties
- Leaves no residue
- Neutral non-conductive
- Non-corrosive
- Water-humidity repellent
- Prevents wearing
- Easy to use

APPLICATIONS

Suitable for cleaning and degreasing electrical contacts, cables, switches, batteries, circuit board switches, etc.

METHOD OF APPLICATION

1. Before use, shake the can for 2 minutes and spray a sample.
2. Switch off electrical installations before application.
3. Spray parts until contamination disappears.
4. Switch on the electrical installation after the evaporation of the solvents (5-10 minutes).
5. If needed repeat procedure.
6. After use, turn can upside down and press the nozzle for 5" to clean the valve.

CLEANING

With soap and water immediately after use

CONSUMPTION

3 - 3,8 ml/cm²

TECHNICAL DATA

Form: Liquid

Colour: Transparent

Odour: Characteristic

Relative density: 0,75 gr/ml

Application temperature: 10°C - 30°C

VOC (Volatile Organic Compounds) CONTENT: (Directive 2004/42/CE) EU maximum VOC content limit values for this product (category Be 'Special finishes'): 840 gr/ltr (2010). This product contains maximum 820 gr/ltr VOCs (ready for use product).

STORAGE

In a cool and dry place at temperatures between +5°C - +25°C away from sources of ignition. Avoid direct sunlight.

SHELF LIFE

At least 5 years in unopened original package, under above mentioned storage conditions.

PACKAGING

Spray 400ml

PACKAGING	CODE	BARCODE
400ml	9217	5204094092179

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION



Aerosol 1: H229 - Pressurized container: May burst if heated
Aerosol 1: H222 - Extremely flammable aerosol Eye Irrit. 2: H319 - Causes serious eye irritation STOT SE 3: H336 - May cause drowsiness or dizziness P101: If medical advice is needed, have product container or label at hand P102: Keep out of reach of children P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P211: Do not spray on an open flame or other ignition source P251: Do not pierce or burn, even after use P280: Wear protective gloves/protective clothing/eye protection/face protection P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F P501: Dispose of contents and / or their container according to the separated collection system used in your municipality. Substances that contribute to the classification: Propan-2-ol; 1-methoxy-2-propanol; N-hexane

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.

