



Wood Protection & Treatment

T-WAX

Technical Data Sheet

Reviewed: 06.06.2015



DESCRIPTION

T-WAX is wood wax treatment with cleaning and nourishing action. The special blend of natural waxes enriched with silicone is excellent for nourishing and cleaning wooden surfaces. It produces a rich, satiny luster. It naturally protects wood and guards against dryness and frequent use.

ADVANTAGES

- Removes finger marks, coffee cup rings etc.
- Protects wood against dryness
- Produces a rich, satiny luster
- Suitable for a variety of surfaces

APPLICATIONS

- Ideal for nourishing unsealed wooden surfaces
- Protects polished woods, lacquered surfaces, plastics, ceramic wall tiles, vinyl upholstery, leather and metal.
- Suitable for most wooden surfaces such as antique furniture, floors, cupboards, doors, woodcarvings, claddings, accessories where a tough protective varnished surface is not required.

INSTRUCTIONS FOR USE

1. Ensure the surface is clean, dry and free from dust and oily residues
2. Apply T-WAX evenly with a soft, lint-free cotton cloth
3. Allow to dry for 30 – 60 minutes or till wax is absorbed
4. Buff with a clean lint-free cotton cloth till the surface shines
5. Repeat the operation for higher protection and shine
6. Always test product on an inconspicuous area for compatibility and end result.

Cleaning and maintenance: wipe over with a cloth or duster and re-wax as required when the surface looks dull and tired. Do not wash with water.

Precautions: not suitable for high water areas such as kitchens and bathrooms.

CLEANING

Clean tools immediately after use with white spirit

COVERAGE

50-200 gr/m² depending on wood absorption

TECHNICAL CHARACTERISTICS

Base: Blend of waxes
Form: Thixotropic paste
Color: Off-white
Odor: Waxy aromatic
Specific gravity: 0,735 –0,750 gr/ml 25°C
Viscosity: High viscosity paste
Flammability: Flammable
Dilution: Organic solvents
Application method: Cloth
Application temperature: +5°C έως +35°C

STORAGE

In a cool and dry place at temperatures between +5°C - +30°C. Protect from direct sunlight and frost.

SHELF LIFE

At least 12 months in unopened packaging in the above mentioned storage conditions

PACKAGING

375ml

PACKAGING	CODE	BARCODE
375ml	5657	5204094056201

HEALTH AND SAFETY INFORMATION

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects **P101:** If medical advice is needed, have product container or label at hand **P102:** Keep out of reach of children **P103:** Read label before use **P273:** Avoid release to the environment **P501:** Dispose of the contents/containers in accordance with the current legislation on waste treatment

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



Evochem®

EVOCHEM S.A.
Tzaverdella place 13341, Fyli, Attica, Greece
Tel.: 210 5590460, 210 5590155 Fax: 210 5590244
E-mail: info@evochem.gr Website: www.evochem.gr

