

Betofix[®] Waterstop

Description of the product

Solvent based paint for the protection of moist surfaces.

Applications

Betofix[®] Waterstop is suitable for for the protection of moist surfaces in basements, walls, air conditioning rooms.

Properties/Advantages

- It is simple to implement and does not require special care in the preparation of the surface
- Displays excellent adhesion even on porous or alkaline substrates
- Capable of withstanding increased negative pressures
- Resistant to washing detergent
- Non-yellowing

Technical Characteristics

Density (25 ^o C)	1,42 kg/l
Flash point	+42 ^o C
Consumption	500gr/m ² for 2 coats
Drying time (25 ^o C)	4-5 hours
Ambient Temperature	From +5 ^o C to +35 ^o C
Overcoating time (25 ^o C)	24 hours

Instruction for use

Surface preparation: The substrate should be clean, dry and free from dust, oil, grease, or any poorly adhering material.

Betofix[®] Waterstop

Application:

Stir the product thoroughly in its container. Apply two coats of **Betofix[®] Waterstop** by brush or roller. Dilute with solvent **Neotex 1080** (10-15%).

Notes

If there is an increased negative pressure it is recommended to apply first the cement-based brushable waterproofing system **Neopress[®]** reinforced with emulsion **Revinex[®]** by creating openings reliefs. After the closure of these openings apply **Betofix[®] Waterstop**

Colours

White

Packaging

Cans of 1kg and 5kg

Cleaning of tools

Use Solvent **Neotex 1080**

Stain removal

Use Solvent **Neotex 1080**

Storage stability

The product is stable for 2 years when kept unopened in its original container, protected from frost and direct sunlight.