### **ACRYLIC PUTTY**

Revision nr.2 Dated 26/02/2015 Printed on 16/11/2015 Page n. 1 / 7

# Safety data sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ACRYLIC PUTTY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Acrylic putty

1.3. Details of the supplier of the safety data sheet

Name VITEX - HERMES YANNIDIS BROS S.A.

Full address IMEROS TOPOS

District and Country 19300 ASPROPYRGOS (ATTIKI)

GREECE

Tel. (0030) 2105589400 Fax (0030) 2105597859

e-mail address of the competent person

responsible for the Safety Data Sheet vitexlab@vitex.gr

Product distribution by YANNIDIS BROS S.A.

1.4. Emergency telephone number

For urgent inquiries refer to (0030) 2105589400

(0030) 2107793777

### **SECTION 2. Hazards identification.**

#### 2.1. Classification of the substance or mixture.

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.

### 2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication: --

### 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

Signal words: --

Hazard statements:

**EUH210** Safety data sheet available on request.

**EUH208** Contains: 5-Chloro-2-methyl- 3(2H)-isothiazolone mixture with 2-Methyl- 3(2H)-isothiazolone (3:1)

1,2-benziosothiazolin-3-one

May produce an allergic reaction.

Precautionary statements:

P102 Keep out of reach of children.
P273 Avoid release to the environment.

P301+P312 IF SWALLOWED: Call a POISON CENTER / doctor / . . . / if you feel unwell.

#### 2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### **ACRYLIC PUTTY**

Revision nr.2 Dated 26/02/2015 Printed on 16/11/2015 Page n. 2/7

## **SECTION 3. Composition/information on ingredients.**

#### 3.1. Substances.

Information not relevant.

#### 3.2. Mixtures.

Contains:

EC.

Identification. Conc. %. Classification 67/548/EEC. Classification 1272/2008 (CLP).

1,2-benziosothiazolin-3-one

0 - 0.05CAS. 2634-33-5 220-120-9

T R23, Xn R22, Xi R38, Xi R41, Xi R43, N R50

Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1

INDEX. 613-088-00-6

5-Chloro-2-methyl- 3(2H)-isothiazolone mixture with 2-Methyl- 3(2H)-isothiazolone (3:1)

CAS. *55965-84-9* 0 - 0,0015 T R23/24/25, C R34, Xi R43, N R50/53 Acute Tox. 3 H301+H311+H331, Skin Corr. 1B H314, Skin Sens. 1 H317,

Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 FC

INDEX. 613-167-00-5

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

## **SECTION 4. First aid measures.**

### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

### **SECTION 5. Firefighting measures.**

#### 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

#### 5.3. Advice for firefighters.

**GENERAL INFORMATION** 

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### **ACRYLIC PUTTY**

Revision nr.2 Dated 26/02/2015 Printed on 16/11/2015 Page n. 3 / 7

### **SECTION 6. Accidental release measures.**

#### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

### **SECTION 7. Handling and storage.**

### 7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s).

Information not available.

### **SECTION 8. Exposure controls/personal protection.**

### 8.1. Control parameters.

Information not available.

### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.



## **ACRYLIC PUTTY**

Revision nr.2 Dated 26/02/2015 Printed on 16/11/2015 Page n. 4 / 7

## **SECTION 9. Physical and chemical properties.**

### 9.1. Information on basic physical and chemical properties.

Appearance pasty liquid
Colour white
Odour characteristic
Odour threshold. Not available.
pH. 7-9

Melting point / freezing point. Not available. Initial boiling point. 100 °C. Not available. Boiling range. Flash point. 93 °C. **Evaporation Rate** Not available. Flammability of solids and gases Not available Lower inflammability limit. Not available. Upper inflammability limit. Not available. Lower explosive limit. Not available. Upper explosive limit. Not available. Not available. Vapour pressure. Vapour density Not available.

Relative density. 1,7-1,9 g/ml

Solubility

Partition coefficient: n-octanol/water

Auto-ignition temperature.

Decomposition temperature.

Viscosity

Explosive properties

Oxidising properties

Not available.

Not available.

Not available.

Not available.

Not available.

Not available.

9.2. Other information.

VOC (Directive 1999/13/EC) : Information not available.

## **SECTION 10. Stability and reactivity.**

#### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

### 10.5. Incompatible materials.

Information not available.

# 10.6. Hazardous decomposition products.

Information not available.

### **SECTION 11. Toxicological information.**

## 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product contains sensitizing substance/s and may cause allergic reactions.

1,2-benziosothiazolin-3-one

 $\begin{array}{ll} \text{LD50 (Oral)}. & > 2,175 \text{ mg/Kg } 1,2\text{-benziosothiazolin-3-one} \\ \text{LD50 (Dermal)}. & > 1,221 \text{ mg/Kg } 1,2\text{-benziosothiazolin-3-one} \\ \end{array}$ 

LC50 (Inhalation). 0,5 mg/L

### **ACRYLIC PUTTY**

Revision nr.2 Dated 26/02/2015 Printed on 16/11/2015 Page n. 5 / 7

## **SECTION 12. Ecological information.**

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

#### 12.1. Toxicity.

1,2-benziosothiazolin-3-one

LC50 - for Fish. > 2,18 mg/l/96h 1,2-benziosothiazolin-3-one Oncorhynchus mykiss OECD Test Guideline

203

EC50 - for Crustacea. > 2,94 mg/l/48h 1,2-benziosothiazolin-3-one Daphnia magna OECD Test Guideline 202

EC50 - for Algae / Aquatic Plants. > 0,11 mg/l/72h 1,2-benziosothiazolin-3-one Pseudokirchneriella subcapitata OECD Test

Guideline 201

5-Chloro-2-methyl- 3(2H)-isothiazolone mixture with 2-Methyl- 3(2H)-isothiazolone (3:1)

EC50 - for Crustacea. > 0,018 mg/l/48h

#### 12.2. Persistence and degradability.

Information not available.

#### 12.3. Bioaccumulative potential.

Information not available.

#### 12.4. Mobility in soil.

Information not available.

#### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects.

Information not available.

### **SECTION 13. Disposal considerations.**

### 13.1. Waste treatment methods.

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## **SECTION 14. Transport information.**

#### 14.1. UN number.

Not applicable.

## 14.2. UN proper shipping name.

Not applicable.

### 14.3. Transport hazard class(es).

Not applicable.

### 14.4. Packing group.

Not applicable.

#### 14.5. Environmental hazards.

Not applicable.

### 14.6. Special precautions for user.

Not applicable.

#### ΕN



### **VITEX - HERMES YANNIDIS BROS S.A.**

### **ACRYLIC PUTTY**

Revision nr.2 Dated 26/02/2015 Printed on 16/11/2015 Page n. 6 / 7

## **SECTION 14. Transport information.** .../>>

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

### **SECTION 15. Regulatory information.**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

None.

Substances in Candidate List (Art. 59 REACH).

None

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Information not available.

VOC (Directive 2004/42/EC):

Primers.

VOC given in g/litre of product in a ready-to-use condition :

 Limit value:
 30,00 (2010)

 VOC of product :
 29,00

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

#### **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 3
Acute Tox. 4
Skin Corr. 1B
Eye Dam. 1
Skin Irrit. 2
Skin Sens. 1
Acute toxicity, category 4
Skin corrosion, category 1B
Serious eye damage, category 1
Skin irritation, category 2
Skin sensitization, category 1

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H302 Harmful if swallowed.
H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

**H400** Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

**EUH210** Safety data sheet available on request.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R22 HARMFUL IF SWALLOWED.
R23 TOXIC BY INHALATION.

R23/24/25 TOXIC BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.

R34 CAUSES BURNS. R38 IRRITATING TO SKIN.

R41 RISK OF SERIOUS DAMAGE TO EYES.

R43 MAY CAUSE SENSITISATION BY SKIN CONTACT.

**R50** VERY TOXIC TO AQUATIC ORGANISMS.

### **ACRYLIC PUTTY**

Revision nr.2 Dated 26/02/2015 Printed on 16/11/2015 Page n. 7 / 7

### SECTION 16. Other information. .../>>

R50/53

VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 5. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EU) 453/2010 of the European Parliament
- 7. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 8. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 9. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 10. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 11. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

## Changes to previous review:

The following sections were modified:

01/02/03/08/11/12/16.