



VITEX S.A.

CHASSIS - COAT

Revision nr.7
Dated 29/05/2020
Printed on 04/08/2020
Page n. 1 / 15
Replaced revision:6 (Dated 27/06/2019)

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **CHASSIS - COAT**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Solvent based enamel for metallic surfaces**

1.3. Details of the supplier of the safety data sheet

Name **VITEX S.A.**
Full address **IMEROS TOPOS**
District and Country **19300 ASPROPYRGOS (ATTIKI)**
GREECE
Tel. **(0030) 2105589400**
Fax **(0030) 2105597859**

e-mail address of the competent person responsible for the Safety Data Sheet **vitexlab@vitex.gr**

Product distribution by: **VITEX S.A**

1.4. Emergency telephone number

For urgent inquiries refer to **(0030) 2105589400**
(0030) 2107793777

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Warning**

Hazard statements:
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.



VITEX S.A.

CHASSIS - COAT

Revision nr.7
Dated 29/05/2020
Printed on 04/08/2020
Page n. 2 / 15
Replaced revision:6 (Dated 27/06/2019)

SECTION 2. Hazards identification ... / >>

H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH210	Safety data sheet available on request.
EUH208	Contains: May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P405	Store locked up.
P501	Dispose of contents / container in accordance with local and national regulations.
P264	Wash . . . thoroughly after handling.

Contains: HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS
XYLENE (MIXTURE OF ISOMERS)
HYDROCARBONS, C9, AROMATICS

VOC (Directive 2004/42/EC) :

One-pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition : 495,00

Limit value: 500,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS		
CAS	64742-48-9 25 ≤ x < 30	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	919-857-5	
INDEX	649-327-00-6	
Reg. no.	01-2119463258-33-XXXX	
XYLENE (MIXTURE OF ISOMERS)		
CAS	1330-20-7 9 ≤ x < 10	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C
EC	215-535-7	
INDEX	601-022-00-9	
Reg. no.	01-2119488216-XXXX	
HYDROCARBONS, C9, AROMATICS		
CAS	64742-95-6 6 ≤ x < 7	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	918-668-5	
INDEX	649-356-00-4	
Reg. no.	01-2119455851-35-XXXX	
Reaction mass of ethylbenzene and m-xylene and p-xylene		
CAS	4 ≤ x < 5	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C
EC	905-562-9	
INDEX		



VITEX S.A.

CHASSIS - COAT

Revision nr.7
Dated 29/05/2020
Printed on 04/08/2020
Page n. 3 / 15
Replaced revision:6 (Dated 27/06/2019)

SECTION 3. Composition/information on ingredients ... / >>

Reg. no. 01-2119488216-32-XXXX

TRIZINC BIS (ORTHOPHOSPHATE)

CAS 7779-90-0 $1,54 \leq x < 1,55$ Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 231-944-3

INDEX 030-011-00-6

CALCIUM BIS (2-ETHYLHEXANOATE)

CAS 136-51-6 $0,8 \leq x < 0,9$ Repr. 2 H361d, Eye Dam. 1 H318

EC 205-249-0

INDEX

Reg. no. 01-2119978297-19-XXXX

ZINC BIS(2-ETHYLHEXANOATE)

CAS 85203-81-2 $0,5 \leq x < 0,6$ Repr. 2 H361, Eye Irrit. 2 H319, Skin Irrit. 2 H315

EC 286-272-3

INDEX

HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

CAS 64742-82-1 $0,2 \leq x < 0,3$ Flam. Liq. 3 H226, STOT RE 1 H372, Asp. Tox. 1 H304, STOT SE 3 H336,

Aquatic Chronic 2 H411, EUH066,

Classification note according to Annex VI to the CLP Regulation: P

EC 919-446-0

INDEX 649-330-00-2

Reg. no. 01-2119458049-XXXX

COBALT BIS (2-ETHYLHEXANOATE)

CAS 136-52-7 $0,1 \leq x < 0,2$ Repr. 1B H360F, Eye Irrit. 2 H319, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 3 H412

EC 205-250-6

INDEX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of



VITEX S.A.

CHASSIS - COAT

Revision nr.7
Dated 29/05/2020
Printed on 04/08/2020
Page n. 4 / 15
Replaced revision:6 (Dated 27/06/2019)

contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г (4 Септември 2018г)
CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
HRV	Hrvatska	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/18)
HUN	Magyarország	A pénzügyminiszter 7/2018. (VIII. 29.) PM rendelete a munkahelyek kémiai biztonságáról szóló 25/2000. (IX. 30.) EüM–SZCSM együttes rendelet módosításáról
SVK	Slovensko	Nariadenie vlády č. 33/2018 Z. z. Nariadenie vlády Slovenskej republiky, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 355/2006 Z. z. o ochrane zamestnancov pred rizikami



VITEX S.A.

CHASSIS - COAT

Revision nr.7
Dated 29/05/2020
Printed on 04/08/2020
Page n. 5 / 15
Replaced revision:6 (Dated 27/06/2019)

SECTION 8. Exposure controls/personal protection ... / >>

EU	OEL EU	súvisiacimi s expozíciou chemickým faktorom pri práci v znení neskorších predpisov Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2019

HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	1200				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg/d				
Inhalation			VND	900 mg/m3	VND	1500 mg/m3		
Skin			VND	300 mg/kg/d			VND	300 mg/kg/d

XYLENE (MIXTURE OF ISOMERS)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221		442		SKIN
TLV	CZE	200		400		SKIN
VLEP	FRA	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	
TLV	GRC	435	100	650	150	SKIN
GVI/KGVI	HRV	221	50	442	100	SKIN
AK	HUN	221		442		SKIN
NPEL	SVK	221	50	442		SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

HYDROCARBONS, C9, AROMATICS

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	100				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	11 mg/kg/d				
Inhalation			VND	150 mg/m3			VND	32 mg/m3
Skin			VND	11 mg/kg/d			VND	25 mg/kg/d



VITEX S.A.

CHASSIS - COAT

Revision nr.7
 Dated 29/05/2020
 Printed on 04/08/2020
 Page n. 6 / 15
 Replaced revision:6 (Dated 27/06/2019)

SECTION 8. Exposure controls/personal protection ... / >>

Reaction mass of ethylbenzene and m-xylene and p-xylene

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221		442		SKIN
TLV	CZE	200		400		SKIN
VLEP	FRA	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	
TLV	GRC	435	100	650	150	SKIN
GVI/KGVI	HRV	221	50	442	100	SKIN
AK	HUN	221		442		SKIN
NPEL	SVK	221	50	442		SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND					
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/kg/d 14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

CALCIUM BIS (2-ETHYLHEXANOATE)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	GRC	5000				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	2,83 mg/m3				
Inhalation			VND	9,86 mg/m3			VND	39,98 mg/m3
Skin			VND	2,83 mg/m3			VND	5,67 mg/kg/d

ZINC BIS(2-ETHYLHEXANOATE)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	GRC	5000				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				3,21 mg/kg bw/d				
Inhalation				10,42 mg/m3				20,83 mg/m3
Skin				3,21 mg/kg bw/d				6,41 mg/kg bw/d



VITEX S.A.

CHASSIS - COAT

Revision nr.7
Dated 29/05/2020
Printed on 04/08/2020
Page n. 7 / 15
Replaced revision:6 (Dated 27/06/2019)

SECTION 8. Exposure controls/personal protection ... / >>

HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	350				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	26 mg/kg/d				
Inhalation			VND	71 mg/m3			VND	330 mg/m3
Skin			VND	26 mg/kg/d			VND	44 mg/kg/d

COBALT BIS (2-ETHYLHEXANOATE)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	GRC	5				

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,0095 mg/kg bw/d				
Inhalation				0,0063 mg/m3		0,235 mg/m3		
Skin		NPI						

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.



VITEX S.A.

CHASSIS - COAT

Revision nr.7
Dated 29/05/2020
Printed on 04/08/2020
Page n. 8 / 15
Replaced revision:6 (Dated 27/06/2019)

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	viscous liquid	
Colour	as showed in color folder	
Odour	characteristic	
Odour threshold	Not available	
pH	Not available	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Boiling range	Not available	
Flash point	23 ≤ T ≤ 60 °C	
Evaporation Rate	Not available	
Flammability of solids and gases	Not available	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	Not available	
Vapour density	Not available	
Relative density	1,33-1,37 g/ml	
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
Viscosity	75-85 KU	
Explosive properties	Not available	
Oxidising properties	Not available	

9.2. Other information

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.



VITEX S.A.

CHASSIS - COAT

Revision nr.7
Dated 29/05/2020
Printed on 04/08/2020
Page n. 9 / 15
Replaced revision:6 (Dated 27/06/2019)

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:	> 20 mg/l
LD50 (Oral) of the mixture:	Not classified (no significant component)
LD50 (Dermal) of the mixture:	>2000 mg/kg

Reaction mass of ethylbenzene and m-xylene and p-xylene

LD50 (Oral)	> 2000 mg/kg Rat
LC50 (Inhalation)	> 10 mg/l/4h Rat

XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral)	> 2000 mg/kg Rat
LC50 (Inhalation)	> 10 mg/l/4h Rat

HYDROCARBONS, C9, AROMATICS

LD50 (Oral)	> 2000 mg/kg Rat
LD50 (Dermal)	> 2000 mg/kg Rabbit
LC50 (Inhalation)	> 20 mg/l/4h

HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

LD50 (Oral)	> 5000 mg/kg Rat
LD50 (Dermal)	> 5000 mg/kg Rabbit
LC50 (Inhalation)	> 20 mg/l/4h Rat

HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

LD50 (Oral)	> 5000 mg/kg Rat
LC50 (Inhalation)	> 20 mg/l/4h Rat

TRIZINC BIS (ORTHOPHOSPHATE)

LD50 (Oral)	> 5000 mg/kg Rat - Wistar
LC50 (Inhalation)	> 5,7 mg/l Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

COBALT BIS (2-ETHYLHEXANOATE)

GERM CELL MUTAGENICITY



VITEX S.A.

CHASSIS - COAT

Revision nr.7
Dated 29/05/2020
Printed on 04/08/2020
Page n. 10 / 15
Replaced revision:6 (Dated 27/06/2019)

SECTION 11. Toxicological information ... / >>

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation
May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: 75-85 KU

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

Reaction mass of ethylbenzene and m-xylene and p-xylene

LC50 - for Fish	> 1 mg/l/96h
EC50 - for Crustacea	> 1 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 1 mg/l/72h
Chronic NOEC for Fish	> 1 mg/l based on test data
Chronic NOEC for Crustacea	> 0,1 mg/l

COBALT BIS (2-ETHYLHEXANOATE)

LC50 - for Fish	275 mg/l/96h
EC50 - for Algae / Aquatic Plants	654,2 mg/l/72h

ZINC BIS(2-ETHYLHEXANOATE)

LC50 - for Fish	100 mg/l/96h
EC50 - for Crustacea	5 mg/l/48h
EC50 - for Algae / Aquatic Plants	2,72 mg/l/72h

XYLENE (MIXTURE OF ISOMERS)

LC50 - for Fish	> 1 mg/l/96h
EC50 - for Crustacea	> 1 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 1 mg/l/72h
Chronic NOEC for Fish	> 1 mg/l based on test data
Chronic NOEC for Crustacea	> 0,1 mg/l

HYDROCARBONS, C9, AROMATICS

LC50 - for Fish	> 1 mg/l/96h
EC50 - for Crustacea	> 1 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 1 mg/l/72h
Chronic NOEC for Fish	> 1 mg/l based on modeled data
Chronic NOEC for Crustacea	> 1 mg/l based on modeled data

HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

LC50 - for Fish	> 100 mg/l/96h
EC50 - for Crustacea	> 100 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Fish	> 0,1 mg/l based on modeled data
Chronic NOEC for Crustacea	> 0,1 mg/l based on modeled data



VITEX S.A.

CHASSIS - COAT

Revision nr.7
Dated 29/05/2020
Printed on 04/08/2020
Page n. 11 / 15
Replaced revision:6 (Dated 27/06/2019)

SECTION 12. Ecological information ... / >>

CALCIUM BIS (2-ETHYLHEXANOATE)
LC50 - for Fish 180 mg/l/96h
EC50 - for Crustacea 85,4 mg/l/48h
EC50 - for Algae / Aquatic Plants 49,3 mg/l/72h

HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)
LC50 - for Fish > 1 mg/l/96h
EC50 - for Crustacea > 1 mg/l/48h
EC50 - for Algae / Aquatic Plants > 1 mg/l/72h
Chronic NOEC for Fish > 0,1 mg/l based on modeled data
Chronic NOEC for Crustacea > 0,1 mg/l based on test data

TRIZINC BIS (ORTHOPHOSPHATE)
LC50 - for Fish 0,78 mg/l/96h Pimephales promelas
EC50 - for Crustacea 0,86 mg/l/48h Daphnia magna

12.2. Persistence and degradability

Reaction mass of ethylbenzene and m-xylene and p-xylene
Rapidly degradable

COBALT BIS (2-ETHYLHEXANOATE)
Entirely degradable

XYLENE (MIXTURE OF ISOMERS)
Rapidly degradable

HYDROCARBONS, C9, AROMATICS
Rapidly degradable

HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS
Rapidly degradable

CALCIUM BIS (2-ETHYLHEXANOATE)
Rapidly degradable

HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)
Rapidly degradable

TRIZINC BIS (ORTHOPHOSPHATE)
Solubility in water 2,7 mg/l
Degradability: information not available

12.3. Bioaccumulative potential

Reaction mass of ethylbenzene and m-xylene and p-xylene
Partition coefficient: n-octanol/water 3,12

XYLENE (MIXTURE OF ISOMERS)
Partition coefficient: n-octanol/water 3,12

HYDROCARBONS, C9, AROMATICS
Partition coefficient: n-octanol/water 3,7

HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS
Partition coefficient: n-octanol/water 5

HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)
Partition coefficient: n-octanol/water 3,7

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.



VITEX S.A.

CHASSIS - COAT

Revision nr.7
Dated 29/05/2020
Printed on 04/08/2020
Page n. 12 / 15
Replaced revision:6 (Dated 27/06/2019)

SECTION 12. Ecological information ... / >>

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 1263

The product, if packaged in packages of less than 450 litres, is not subject to ADR regulations as stated in 2.2.3.1.5.

The product, if packaged in packages of less than 30 litres, is not subject to obligations relating to marking, labelling and package testing in accordance with 2.3.2.5 of the IMDG CODE.

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 30
Special Provision: -

Limited Quantities: 5 L

Tunnel restriction code: (D/E)

IMDG: EMS: F-E, S-E

Limited Quantities: 5 L

IATA: Cargo:

Maximum quantity: 220 L

Packaging instructions: 366

Pass.:

Maximum quantity: 60 L

Packaging instructions: 355

Special Instructions:

A3, A72, A192

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant



VITEX S.A.

CHASSIS - COAT

Revision nr.7
Dated 29/05/2020
Printed on 04/08/2020
Page n. 13 / 15
Replaced revision:6 (Dated 27/06/2019)

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

One-pack performance coatings.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Repr. 1B	Reproductive toxicity, category 1B
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H226	Flammable liquid and vapour.
H360F	May damage fertility.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.



VITEX S.A.

CHASSIS - COAT

Revision nr.7
Dated 29/05/2020
Printed on 04/08/2020
Page n. 14 / 15
Replaced revision:6 (Dated 27/06/2019)

SECTION 16. Other information ... / >>

H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy



VITEX S.A.

CHASSIS - COAT

Revision nr.7
Dated 29/05/2020
Printed on 04/08/2020
Page n. 15 / 15
Replaced revision:6 (Dated 27/06/2019)

SECTION 16. Other information ... / >>

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 10 / 11 / 12.