

# SM-28

## Special solvent for polyurethane-based products

### Description

SM-28 is a specially formulated solvent blend of aromatic hydrocarbons and esters, used in combination with polyurethane-based products.

### Fields of application

Specifically designed for thinning polyurethane-based products (paints, liquid waterproofing membranes, etc.), especially when applied by spray. Also effective for cleaning application tools. Thanks to its special formulation, SM-28 allows for quick drying of the polyurethane material.

### Technical data

Color: clear / colorless  
Density: 0.86 ± 0.02 kg/l

### Directions for use

SM-28 is used for thinning polyurethane materials at a ratio of up to 10% by weight.

### Consumption

Consumption varies depending on the nature of the application.

### Packaging

0.75 l & 4 l containers.

### Shelf life – Storage

12 months from production date, in original, sealed containers, stored at temperatures above 5°C and protected from high temperatures (<+30°C).

### Remarks

- Ensure adequate ventilation when applying SM-28 indoors.
- Keep away from sources of ignition during application – No smoking.
- Please consult the safety instructions written on the packaging before use.
- For further information, please refer to the Material Safety Data Sheet.

#### ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

#### MAIN OFFICES - FACTORY:

17<sup>th</sup> km Thessaloniki - Ag. Athanasios Road,  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,  
Tel.: +30 2310 576 000, Fax: +30 2310 722 475

[www.isomat.eu](http://www.isomat.eu) e-mail: [support@isomat.eu](mailto:support@isomat.eu)