

Vista

Acrylic Paint



Emulsion acrylic paint, for exterior use, based on acrylic copolymer resins. It exhibits great hiding power and high spreading capacity combined with its low cost makes it ideal solution for surfaces that require frequent painting. Easy to apply with very good leveling end produces a smooth flat surface.

- Based on acrylic copolymer resins
- Great hiding power

COLOURS

Available in white and a wide range of shades through Vitex's Colorfull Tinting System.

PACKAGING

White	3 L	9 L	15 L
Bases	3 L	9 L	

SPREADING RATE

10 - 12 m²/L per coat on properly prepared surfaces.

VOC (Volatile Organic Compounds) CONTENT

EU maximum VOC content limit values (Directive 2004/42/CE) for this product (category **A/c** "Exterior walls of mineral substrate", Type **WB**): **40 g/L**. This product contains maximum **39 g/L** VOCs (ready for use product).

SURFACE PREPARATION

Surfaces should be smooth, clean and dry, free from grease, dust, loose or flaking paint.

To fill any cracks or holes use Acrylic Putty.

Surfaces previously covered with water paints or distempers (lime wash or ceiling white) should be primed with Acrylan Unco Eco, Durovit or Vitosin.

New surfaces made of plaster, concrete, cement, plasterboard, etc. should be first primed with Acrylan Unco Eco or Durovit.

APPLICATION

Stir well before use. Apply two coats by roller, brush or airless spray gun diluted up to 10% with water. Do not apply at temperature below 5°C, above 35°C and / or relative humidity above 70%. Avoid application when rain or frost is expected in the next 48 hours.

It is touch-dry after 15-30 minutes and can be recoated after 3-4 hours. Drying time depends on weather conditions (humidity and temperature).

Allow at least 3 weeks before cleaning and washing newly painted surfaces with Vista Acrylic Paint. Wash gently with water using a soft sponge. In case of bad stains, use a mild colourless detergent or soapy water.

Tools must be cleaned immediately after use with water and if needed with soapy water or a detergent.



TECHNICAL CHARACTERISTICS

Viscosity	110 ± 10 KU (ASTM D 562, 25° C)
Density	1,60 ± 0,02 Kg/L (ISO 2811) for white
Gloss	< 5 units @ 60° (ISO 2813)

STORAGE

Containers must be kept closed in a cool, dry, well ventilated area protected from direct sunlight at temperatures between 5°C - 38°C.

SAFETY ADVICE

Read label before use. For further instructions - precautions see Material Safety Data Sheet.



T.Θ. 139 Ημερος Τόπος, Ασπρόπυργος Τ.Κ. 193 00
P.O. Box 139 Imeros Topos, Aspropyrgos GR 193 00
T. + 30 210 5589 500, F. + 30 210 4835 007, www.vitex.gr