

## **Cleaners**

## **CL 32 STRONG ALL PURPOSE CLEANER**

**Technical Data Sheet** 

Reviewed: 30.07.2018



#### **DESCRIPTION**

CL 32 STRONG ALL PURPOSE CLEANER is a strong concentrated all-purpose cleaner for tough stains suitable for professional and household use. Use full strength on hard-to-remove stains or diluted for lighter soiled surfaces. Removes effectively soil and stains from oil, grease, salt, wine, coffee, soot and much more. Suitable for interior and exterior use.

#### **ADVANTAGES**

- Extremely strong concentrated formula
- Removes difficult stains
- May be used diluted for daily use

#### **APPLICATIONS**

Cleans fast and effectively ceramic tiles, marble, mosaic, PVC floors, car and boat engines, car wheels and tires, plastic boats, balconies, flowerpots, sanitary ware, plastic furniture, electrical equipment, work tops, barbecues, walls, wallpaper, carpets and much more. Can be used with pressure washer.

#### **INSTRUCTIONS FOR USE**

Shake product well before using.

### Surface cleaning

- Use cleaner full strength for heavy duty cleaning or dilute up to 70% with clean water for general cleaning in which case may be used with a sprayer.
- Apply cleaner with a clean sponge and allow to soak for 2-5 minutes.
- 3. Rub surface if needed.
- 4. Do not allow to dry on surface.
- Rinse well with clean water.

#### Floor cleaning

- 1. Dissolve 50 ml in half a bucket (5Lt) of lukewarm water.
- Clean the floor with a wrung-out mop or floor cloth, regularly rinsing it in the cleaning solution.
- It is advisable to mop the clean surface with clean water before drying.

#### **CONSUMPTION**

Depends on dilution

#### **TECHNICAL CHARACTERISTICS**

Form: Liquid Color: Yellow

Odour: Characteristic of alkalis Density: 1,13 ± 0.02 gr/cm<sup>3</sup>25 °C Flammability: Non Flammable Solubility in water: Unlimited

Application temperature: +5°C έως +35°C

#### **REMARKS**

- Before use, test on an inconspicuous place.
- Avoid spraying on open sockets and electricity wires.
- Do not use on cooking, eating or direct food contact surfaces.

#### STORAGE

Products should be stored in a dry and cool place at a temperature of 5°-35°C. Protect from humidity and direct sunlight.

#### SHELF LIFE

12 months from the production date in the above mentioned storage conditions. The product should remain in the original unopened packaging bearing the manufacturer's batch number.

#### **PACKAGING**

Plastic container 1Lt & 4Lt

PACKAGING	CODE	BARCODE
1Lt	5196	5204094051961
4Lt	5197	5204094051978

#### **HEALTH AND SAFETY INFORMATION**



Skin Corr. 1A: H314 - Causes severe skin burns and eye damage P101: If medical advice is needed, have product container or label at hand P260: Do not breathe vapours P264: Wash the hands thoroughly after handling P280: Wear protective gloves/protective clothing/eye protection/face protection P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

# **Evochem®**

**EVOCHEM S.A.** 

Tzaverdella place 13341, Fyli, Attica, Greece Tel.: 210 5590460, 210 5590155 Fax: 210 5590244 E-mail: info@evochem.gr Website: www.evochem.gr











## **Cleaners**

## **CL 32 STRONG ALL PURPOSE CLEANER**

**Technical Data Sheet** 

Reviewed: 30.07.2018

do. Continue rinsing P390: Absorb spillage to prevent material damage P403+P233+P102+P405: Store in a well-ventilated place. Keep container tightly closed. Keep out of reach of children. Store locked up P501: Dispose of contents/container according to the separated collection system used in your municipality. Substances that contribute to the classification: Tetrasodium ethylenediaminetetraacetate; Potassium hydroxide; Poly (oxy-1,2-ethanediyl), .alpha.hydroxide; carboxymethyl-.omega.-hexyloxy- (3 mol EO average molar ratio)

> The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.

**TECHNICAL SUPPORT** 210.5590460 MONDAY TO FRIDAY 8:00 - 16:00



EVOCHEM S.A.

Tzaverdella place 13341, Fyli, Attica, Greece Tel.: 210 5590460, 210 5590155 Fax: 210 5590244 E-mail: info@evochem.gr Website: www.evochem.gr







