



### DESCRIPTION

**GOLD METALLIC** is a gold metallic paint ideal for decoration and protection of most surfaces. It can be applied on metal, wood, carton, plaster, canvas and most plastic surfaces. It offers anticorrosive protection, very good coverage, excellent surface adhesion properties and a smooth finish. It is suitable for interior and exterior use.

### ADVANTAGES

- Very good coverage
- Excellent adhesion
- Smooth finish
- Colour stability
- Lead free
- Easy application

### APPLICATIONS

- Protection and decoration of various surfaces
- Ideal for festive decorations, ornaments, rails, mirrors and much more
- It is suitable for most surfaces such as metal, wood, carton, plaster, canvas and most plastic surfaces

### INSTRUCTIONS FOR USE

#### Surface Preparation

All surfaces should be sanded, dry and clean from dirt, rust, grease, loose paint etc.

#### Application

##### Metal surfaces

Apply two coats of SWAN RUST PRIMER or SWAN MINIO for anti-corrosion protection.

Follow with application of one or two coats of **GOLD METALLIC** according to application.

##### Other surfaces

Apply directly one or two coats of **GOLD METALLIC** according to application.

### LEAD STATEMENT

**WARNING:** Treatment of old surfaces such as dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Lead dust may be released.

Lead is toxic. Exposure to lead dust can cause serious illness. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

### CLEANING

Clean all equipment immediately after use with nitro solvent or general purpose thinner.

### COVERAGE

10 - 14 m<sup>2</sup>/lt

### TECHNICAL CHARACTERISTICS

**Type:** Solvent based paint

**Specific gravity:** 1,02 gr/cm<sup>3</sup> 25°C

**Viscosity:** 150 cps 25°C

**Method of application:** Brush, roller or airless spray

**Application temperature:** 10°C - 35°C

**Thinning:** Ready for use

**Drying times:** touch dry 20 - 30 minutes

**VOC (Volatile organic Compounds) CONTENT:** (Directive 2004/42/CE) EU maximum VOC content limit values for this product (category A/i(SB) One-pack performance coatings-anticorrosion finishes"): 500gr/lt (2010). This product contains maximum 480gr/lt VOCs (ready for use product).

### STORAGE

Products should be stored in a dry and cool place at a temperature of 5°C -35°C, away from sources of ignition. Protect from humidity and direct sunlight.

### SHELF LIFE

24 months from the production date in the above mentioned storage conditions. The product should remain in the original unopened packaging bearing the manufacturer's batch number.

### PACKAGING

180ml

PACKAGING	CODE	BARCODE
180ml	09032	5204094090328

### HEALTH AND SAFETY INFORMATION



Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled Flam. Liq. 3: H226 - Flammable liquid and vapour Skin Irrit. 2: H315 - Causes skin irritation P101: If medical advice is needed, have product container or label at hand P102: Keep out of reach of children P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P264: Wash thoroughly after handling P280: Wear protective gloves/protective clothing/eye protection/face protection P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing P370+P378: In case of fire: Use ABC powder extinguisher to extinguish. P501: Dispose of contents and / or their container according to the separated collection system used in your municipality Substances that contribute to the classification: Xylene (CAS: 1330-20-7)

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.

