

# Vista

## Distemper Paint



Distemper (ceiling white) water-based paint for interior use, suitable for ceilings of bathrooms and kitchens, staircases, storehouses and generally where washing is not needed. It provides great hiding power, good spreading rate and superior whiteness, while at the same time allows surfaces to "breathe".

- **Great hiding power**
- **For ceilings of kitchens, staircases, storehouses**

### COLOURS

Available in white.

### PACKAGING

White	3 L	9 L	15 L
-------	-----	-----	------

### SPREADING RATE

10 - 12 m<sup>2</sup>/L per coat on properly prepared surfaces.

### VOC (Volatile Organic Compounds) CONTENT

EU maximum VOC content limit values (Directive 2004/42/CE) for this product (category **A/a** "Interior matt walls and ceilings (Gloss<25@60°)", Type **WB**): **30 g/L**. This product contains maximum **14 g/L** VOCs (ready for use).

### SURFACE PREPARATION

Surfaces should be smooth, clean and dry, free from grease, dust, loose or flaking paint.

### APPLICATION

Stir well before use. Apply two coats by roller, brush or airless spray gun diluted up to 10-20% with water. Do not apply at temperature below 5°C, above 35°C and/or relative humidity above 80%.

It is touch-dry after 30-60 minutes and can be recoated after 3-4 hours. Drying time depends on weather conditions (humidity and temperature).

Tools must be cleaned immediately after use with water and if needed with soapy water or a detergent.



### TECHNICAL CHARACTERISTICS

Viscosity	125 ± 10 KU (ASTM D 562, 25°C)
Density	1,57 ± 0,02 Kg/L (ISO 2811)
Gloss	< 5 units @ 60° (ISO 2813)

### STORAGE

Containers must be kept closed in a cool, dry, well ventilated area protected from direct sunlight at temperatures between 5°C - 38°C.

### SAFETY ADVICE

Read label before use. For further instructions - precautions see Material Safety Data Sheet.



T.Θ. 139 Ημερος Τόπος, Ασπρόπυργος Τ.Κ. 193 00  
P.O. Box 139 Imeros Topos, Aspropyrgos GR 193 00  
T. + 30 210 5589 500, F. + 30 210 4835 007, www.vitex.gr