

# Paint Remover



Extremely active paint and varnish remover based on new technology without dichloromethane. Removes from any surface old one or two component paints penetrating into their film, without affecting it.

- Removes one or two component paints
- Without affecting the surface
- Without dichloromethane

## PACKAGING

Colorless	375 mL	750 mL
-----------	--------	--------

## SPREADING RATE

2 – 4 m<sup>2</sup>/L depending on the coating and type of surface.

## APPLICATION

Open container with care. Apply by brush or spatula a thick layer without dilution and let it act for 10-20 minutes (in paints or varnishes two components allow to act for longer). Then with a spatula or scraper remove the soft paint. Repeat the process if necessary. Do not apply at temperature below 5°C and above 35°C.

It is dry in 15 - 40 minutes, depending on atmospheric conditions. After removal of old paint or varnish, clean the surface with water or thinner and after drying can be recoated.

Clean brushes, spatulas and floor stains with water and then with soap or detergent.



## TECHNICAL CHARACTERISTICS

Density	0,99 ± 0,02 Kg/L (ISO 2811)
---------	-----------------------------

## STORAGE

Containers must be kept closed in a cool, dry, well ventilated area protected from direct sunlight at temperatures between 5°C - 38°C.

## SAFETY ADVICE

Read label before use. For further instructions - precautions see Material Safety Data Sheet.



T.Θ. 139 Ημερος Τόπος, Ασπρόπυργος Τ.Κ. 193 00  
P.O. Box 139 Imeros Topos, Aspropyrgos GR 193 00  
T. + 30 210 5589 500, F. + 30 210 4835 007, www.vitex.gr