

# SHELLAC/GASKET CEMENT



## PROPERTIES

Genuine shellac/gasket cement, reinforced with resins. It presents high bonding power, resistance to temperatures and UV radiation. A sealant and an adhesive for gaskets and plumbing connections that dries quickly. It prevents the corrosion of metal surfaces and protects from alkalis. The container cap has a built-in round brush for easy applications.

## APPLICATIONS

DUROSTICK SHELLAC/GASKET CEMENT, seals the pores created in the seams of oil and water tanks after their welding as well as in car tanks that have rusted inside.

Suitable for all metal containers that come in contact with water, oil, gasoline, synthetic and mineral oils. Provides additional protection against leaks where permite flanges, seals and threads are installed.

Resistant to alkalis and in combination with its unique resistance against oil products and salt, it protects the decks and the cargo holds of ships by creating a barrier.

It is also suitable for coating over wood knots, preventing the peeling and cracking of enamel paints and varnishes.

It is used as a high-strength varnish for antique furniture and musical instruments, when diluted with denatured alcohol.

## USE

### 1. Surface preparation

Clean rust spots with emery paper, wire brush or steel wool. Then, remove any oil residue, fat and grease with white spirit or DUROSTICK THINNER 101.

### 2. Application

Apply with the brush attached to the cap, one to two coats with a difference of one hour between each coat. For larger applications, use a painting brush or a roller

## NOTE

After curing, the product is harmless to health.

## CONSUMPTION

150-200ml/m<sup>2</sup> per coat

# SHELLAC/GASKET CEMENT



## STORAGE

Store in tightly closed container, in shaded places, away from any heat source, for at least 18 months from production date.

## SAFETY DIRECTIONS

The product is classified as highly flammable and toxic. It is recommended to keep it locked, away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

## PACKAGING

Carton box with 12 pcs of 60ml each one  
Carton box with 12 pcs of 200ml each one

### TECHNICAL SPECIFICATIONS

<b>Form - Color</b>	Thick liquid - Honey brown
<b>Density</b>	1.00±0.05kg/lit
<b>Temperature resistance</b>	From -20°C to +110°C
<b>Application temperature</b>	From +4°C to +40°C
<b>Dilution-Cleaning</b>	Only with denatured alcohol or ethanol

## DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS  
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612  
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 10, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367  
Email: [info@durostick.com](mailto:info@durostick.com)