

ATHENS: V. Moira str., P.O. Box 2315, GR 19600 Industrial Area Mandra, Athens, Greece, Tel.: +30 210 5557579, Fax: +30 210 5558482  
THESSALONIKI: Ionias Str., GR 57009 Kalochori, Thessaloniki, Greece, Tel.: +30 2310 467275, Fax: +30 2310 463442

## Neotex<sup>®</sup> PU 0413

### Thinner for PU and PAS paint

|                                  |  |
|----------------------------------|--|
| <b>Fields of Application</b>     | <p>Thinner for the polyurethane coating <b>Neodur<sup>®</sup> Special</b>.</p> <p>Also used for the dilution of the solvent-free polyurea resin <b>Neodur<sup>®</sup> Polyurea M</b> for the material to be used as primer, prior to the application of <b>Neodur<sup>®</sup> FT Clear</b> (if needed)</p> <p>If needed, <b>Neotex<sup>®</sup> PU 0413</b> is used for the dilution of polyaspartic polyurea coatings, such as <b>Neoproof<sup>®</sup> Polyurea</b> and <b>Neodur<sup>®</sup> Fast Track</b>.</p> <p><b>Neotex<sup>®</sup> PU 0413</b> is suitable for the cleaning of surfaces or tools, after the application of the above products.</p> |
| <b>Technical Characteristics</b> |  |
| <b>Appearance</b>                | Transparent liquid   |
| <b>Density</b>                   | 0,88 kg/l  |
| <b>Packing</b>                   | Cans of 1kg  |
| <b>Storage Stability</b>         | 2 years in sealed tin cans, kept in shade and away from combusive sources.   |
| <b>Safety Precautions</b>        | See Safety Data Sheets.  |