

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **BRUSH SOLVENT T 300**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Organic solvent suitable for thinning coatings and primers.**

1.3. Details of the supplier of the safety data sheet

Name **VITEX - HERMES YANNIDIS BROS S.A.**
 Full address **IMEROS TOPOS**
 District and Country **19300 ASPROPYRGOS (ATTIKI)**
GREECE
 Tel. **(0030) 2105589400**
 Fax **(0030) 2105597859**

e-mail address of the competent person responsible for the Safety Data Sheet

vitexlab@vitex.gr

Product distribution by **YANNIDIS BROS S.A.**

1.4. Emergency telephone number

For urgent inquiries refer to **(0030) 2105589400**
(0030) 2107793777

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Specific target organ toxicity - repeated exposure, category 3	H372	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 2	H411	Toxic to aquatic life with long lasting effects.

2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.

Danger Symbols: **Xn-N**

R phrases: **10-51/53-65-66-67**

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



BRUSH SOLVENT T 300
SECTION 2. Hazards identification. ... / >>

Signal words: Danger

Hazard statements:

H226 Flammable liquid and vapour.
H372 Causes damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust / fume / gas / mist / vapours / spray.
P271 Use only outdoors or in a well-ventilated area.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER / doctor / . . .
P331 Do NOT induce vomiting.
P405 Store locked up.
P501 Dispose of contents / container to . . .

Contains: HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.
3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
-----------------	----------	----------------------------	---------------------------------

HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

CAS. 64742-82-1 EC. 919-446-0 INDEX. 649-330-00-2 Reg. no. 01-2119458049-XXXX	90 - 99 R10, R66, R67, Xn R65, N R51/53, Note P	Flam. Liq. 3 H226, STOT RE 1 H372, Asp. Tox. 1 H304, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Note P
--	--	--

HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

CAS. 64742-48-9 EC. 919-857-5 INDEX. 649-327-00-6 Reg. no. 01-2119463258-XXXX	5 - 9 R10, R66, R67, Xn R65, Note P	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Note P
--	--	---

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

SECTION 4. First aid measures.
4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

BRUSH SOLVENT T 300
SECTION 5. Firefighting measures.
5.1. Extinguishing media.
SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.
HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters.
GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health.

Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.
6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.
7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

SECTION 8. Exposure controls/personal protection.
8.1. Control parameters.

Regulatory References:

EU OEL EU Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.

BRUSH SOLVENT T 300
SECTION 8. Exposure controls/personal protection. ... / >>
HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)
Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm

OEL EU 350

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers.		Effects on workers					
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.			VND	26 mg/kg/d				
Inhalation.			VND	71 mg/m ³			VND	330 mg/m ³
Skin.			VND	26 mg/kg/d			VND	44 mg/kg/d

HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS
Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm

OEL EU 1200

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers.		Effects on workers					
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.			VND	300 mg/kg/d				
Inhalation.			VND	900 mg/m ³	VND	1500 mg/m ³		
Skin.			VND	300 mg/kg/d			VND	300 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
 VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards. Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The 'work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

BRUSH SOLVENT T 300
SECTION 9. Physical and chemical properties.
9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	colourless
Odour	characteristic of solvent
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	> 162 °C.
Boiling range.	Not available.
Flash point.	> 42 °C.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	0,7 % (V/V).
Upper explosive limit.	6,5 % (V/V).
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	0,78-0,79 Kg/m3
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	<30 secs (ISO cup 3 23C)
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

Information not available.

SECTION 10. Stability and reactivity.
10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information.
11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product may cause functional disorders or morphological mutations after repeated or prolonged exposure and/or may accumulate inside the human body and is thus graded as dangerous.

The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

This product may have a degreasing action on the skin, producing dryness and chapped skin after repeated exposure.

BRUSH SOLVENT T 300
SECTION 11. Toxicological information. ... / >>

HYDROCARBONS, LD50 (Oral). LD50 (Dermal). LC50 (Inhalation).	C9-C11, > 5000 mg/kg Rat > 5000 mg/kg Rabbit > 20 mg/l/4h Rat	n-ALKANES,	ISOALKANES,	CYCLICS,	<2%	AROMATICS
---	--	------------	-------------	----------	-----	-----------

HYDROCARBONS, LD50 (Oral). LC50 (Inhalation).	C9-C12, > 5000 mg/kg Rat > 20 mg/l/4h Rat	n-ALKANES,	ISOALKANES,	CYCLICS,	AROMATICS	(2-25%)
---	---	------------	-------------	----------	-----------	---------

SECTION 12. Ecological information.

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

12.1. Toxicity.

HYDROCARBONS, LC50 - for Fish. EC50 - for Crustacea. EC50 - for Algae / Aquatic Plants. Chronic NOEC for Fish. Chronic NOEC for Crustacea.	C9-C11, > 100 mg/l/96h > 100 mg/l/48h > 100 mg/l/72h > 0,1 mg/l based on modeled data > 0,1 mg/l based on modeled data	n-ALKANES,	ISOALKANES,	CYCLICS,	<2%	AROMATICS
---	---	------------	-------------	----------	-----	-----------

HYDROCARBONS, LC50 - for Fish. EC50 - for Crustacea. EC50 - for Algae / Aquatic Plants. Chronic NOEC for Fish. Chronic NOEC for Crustacea.	C9-C12, > 1 mg/l/96h > 1 mg/l/48h > 1 mg/l/72h > 0,1 mg/l based on modeled data > 0,1 mg/l based on test data	n-ALKANES,	ISOALKANES,	CYCLICS,	AROMATICS	(2-25%)
---	--	------------	-------------	----------	-----------	---------

12.2. Persistence and degradability.

HYDROCARBONS, Rapidly biodegradable.	C9-C11,	n-ALKANES,	ISOALKANES,	CYCLICS,	<2%	AROMATICS
---	---------	------------	-------------	----------	-----	-----------

HYDROCARBONS, Rapidly biodegradable.	C9-C12,	n-ALKANES,	ISOALKANES,	CYCLICS,	AROMATICS	(2-25%)
---	---------	------------	-------------	----------	-----------	---------

12.3. Bioaccumulative potential.

HYDROCARBONS, Partition coefficient: n-octanol/water.	C9-C11,	n-ALKANES, 5	ISOALKANES,	CYCLICS,	<2%	AROMATICS
--	---------	-----------------	-------------	----------	-----	-----------

HYDROCARBONS, Partition coefficient: n-octanol/water.	C9-C12,	n-ALKANES, 3,7	ISOALKANES,	CYCLICS,	AROMATICS	(2-25%)
--	---------	-------------------	-------------	----------	-----------	---------

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.
13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

BRUSH SOLVENT T 300
SECTION 14. Transport information.
14.1. UN number.

ADR / RID, IMDG, IATA: UN: 1263

14.2. UN proper shipping name.

 ADR / RID: PAINT or PAINT RELATED MATERIAL
 IMDG: PAINT or PAINT RELATED MATERIAL
 IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es).

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3


14.4. Packing group.

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards.

ADR / RID: Environmentally Hazardous.



IMDG: Marine Pollutant.



IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6. Special precautions for user.

ADR / RID:	HIN - Kemler: 30	Limited Quantities: -	Tunnel restriction code: -
	Special Provision: -		
IMDG:	EMS: -	Limited Quantities: -	
IATA:	Cargo:	Maximum quantity: -	Packaging instructions: -
	Pass.:	Maximum quantity: -	Packaging instructions: -
	Special Instructions:	-	

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.
Seveso category. 9ii, 6

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.
Product
 Point. 3 - 40

Substances in Candidate List (Art. 59 REACH).

BRUSH SOLVENT T 300**SECTION 15. Regulatory information. ... / >>**

None.
Substances subject to authorisation (Annex XIV REACH).
None.
Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:
None.

Substances subject to the Rotterdam Convention:
None.

Substances subject to the Stockholm Convention:
None.

Healthcare controls.
Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Product not intended for uses provided for by Dir. 2004/42/CE.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H226	Flammable liquid and vapour.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R10	FLAMMABLE.
R51/53	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
R65	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.
R66	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.
R67	VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value

BRUSH SOLVENT T 300**SECTION 16. Other information. ... / >>**

- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments
2. Directive 67/548/EEC and following amendments and adjustments
3. Regulation (EU) 1907/2006 (REACH) of the European Parliament
4. Regulation (EU) 1272/2008 (CLP) of the European Parliament
5. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
6. Regulation (EU) 453/2010 of the European Parliament
7. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
8. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
9. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
10. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
11. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

02 / 07 / 08 / 09 / 11 / 14 / 15.