

Jointex®

Elastomeric acrylic mastic for sealing joints

Properties	Jointex® exhibits high elasticity and excellent adhesion on a variety of substrates. It has high resistance to UV radiation and is resistant to aging. It can be overcoated with water-based paints and coatings. It is resistant to dilute acids, alkalis and detergents. It does not contain any solvents and is environmentally friendly
-------------------	--

Technical Characteristics

Appearance	Homogeneous paste
Density	1,5g/cm ³
Hardness (Shore A)	20±3
Elongation (+25°C)	250%
Shrinkage	3,5%
Consumption	~150gr/lin.m. for joints 1x1cm

Instructions for use	<p><i>Surface preparation:</i> The surface must be stable, clean, dry, protected from rising moisture and free of dust, oils, grease and loose materials. Any loose materials and older coatings must be carefully removed and the surface should be thoroughly cleaned, mechanically or chemically.</p> <p><i>Application:</i> Jointex® is applied by smooth trowel. In the case of joints, it is advisable to install a suitable backing rod, depending on the depth of the joint, and it is recommended to place self-adhesive paper tape along the two sides of the joint and remove it immediately after sealing</p>
-----------------------------	--

Notes	<ul style="list-style-type: none">• <i>Application conditions:</i> Ambient temperature: +12°C min. / +35°C max.• Jointex® should not be applied under wet conditions, or if wet conditions are expected to prevail during the curing period of the product.• After its application, Jointex® presents slight shrinkage• In the case of horizontal joints sealed with Jointex® where there is a possibility of accumulation of ponding water, it is recommended that the joints are subsequently coated with suitable water-based waterproofing coatings (e.g. Neorooft®, Neoproof® PU W, Silatex® Super).
--------------	---

Cleaning of tools	By water immediately after application
--------------------------	--

Stain removal	By water immediately when the stain is still fresh and damp. In case of hardened stains, use mechanical means or a paint remover.
----------------------	---

Jointex®

Colours	White and terracotta.
Packing	1 kg, 5 kg & 15 kg plastic containers
Safety Precautions	See Safety Data Sheets.
Storage stability	2 years, stored in its original sealed packing, protected from frost, humidity and exposure to sunlight.