

WATER BASED FLOOR PRIMER

ΕN

Safety data sheet SECTION 1. Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier WATER BASED FLOOR PRIMER Product name 1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use Water based one component transparent acrylic floor primer 1.3. Details of the supplier of the safety data sheet VITEX - HERMES YANNIDIS BROS S.A. Name Full address **IMEROS TOPOS** 19300 ASPROPYRGOS District and Country (ATTIKI) GREECE Tel. (0030) 2105589400 (0030) 2105597859 Fax e-mail address of the competent person responsible for the Safety Data Sheet vitexlab@vitex.gr Product distribution by YANNIDIS BROS S.A. 1.4. Emergency telephone number For urgent inquiries refer to (0030) 2105589400

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.

(0030) 2107793777

2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

Signal words:

Hazard statements: EUH208

1.2-benziosothiazolin-3-one May produce an allergic reaction.

Precautionary statements:

P102	Keep out of reach of children.
P273	Avoid release to the environment.
P301+P312	IF SWALLOWED: Call a POISON CENTER / doctor / / if you feel unwell.

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

Contains:

3.1. Substances.

Information not relevant.



WATER BASED FLOOR PRIMER

Revision nr.2 Dated 26/02/2015 Printed on 16/11/2015 Page n. 2 / 7 ΕN

SECTION 3. Composition/information on ingredients. .../>>

3.2. Mixtures.

Contains:

Identifica	tion.	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
CAS. EC. INDEX.	YETHANOL 111-76-2 203-905-0 603-014-00-0 01-21194751		Xn R20/21/22, Xi R36/38	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.



WATER BASED FLOOR PRIMER

Revision nr.2 Dated 26/02/2015 Printed on 16/11/2015 Page n. 3 / 7

SECTION 6. Accidental release measures. .../>>

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА
		ЗДРАВЕОПАЗВАНЕТО НАРЕДБА № 13 от 30 декември 2003 г
CYP	Κύπρος	К.Δ.П. 268/2001; К.Δ.П. 55/2004; К.Δ.П. 295/2007; К.Δ.П. 70/2012
CZE	Česká Republika	Nařízení vlády č. 361/2007 Sb. kterým se stanoví podmínky ochrany zdraví při práci
GRB	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
HRV	Hrvatska	NN13/09- Institut za sigurnost Zagreb
HUN	Magyarország	50/2011. (XII. 22.) NGM rendelet a munkahelyek kémiai biztonságáról
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2014

				2-BUTOX	YETHANOL				
Threshold Limit Va	alue.								
Туре	Country	TWA	/8h	STEL/15r	nin				
		mg/m	n3 ppm	mg/m3	ppm				
TLV	BGR	98		246			SKIN.		
TLV	CYP	98	20	246	50		SKIN.		
TLV	CZE	100		200			SKIN.		
WEL	GRB	123	25	246	50		SKIN.		
TLV	GRC	120	25						
GVI	HRV	98	20	246	50		SKIN.		
MDK	HRV	25	5						
AK	HUN	98		246					
OEL	EU	98	20	246	50		SKIN.		
TLV-ACGIH		97	20						
Predicted no-effec	t concentr	ation - P	NEC.						
Normal value in	fresh wate	r					8,8	mg/L	
Normal value of	STP micro	organisn	ns				463	mg/L	
Normal value fo	r the terres	trial com	partment				2,8	mg/Kg	
Health - Derived no	o-effect lev	el - DNE	L / DMEL						
	Eff	ects on c	onsumers.			Effects on wo	orkers		
Route of exposu	ure Aci	ute local	Acute	Chronic local	Chronic	Acute local	Acute sys	temic Chronic	Chronic
			systemic		systemic			local	systemic
Oral.	VN	D	13,4						
			mg/Kg						
Inhalation.	VN	D	426			VND	663		
			mg/m3				mg/m3		
Skin.	VN	D	44,5			VND	89		
			mg/Kg				mg/Kg		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

ΕN



WATER BASED FLOOR PRIMER

Revision nr.2 Dated 26/02/2015 Printed on 16/11/2015 Page n. 4 / 7

SECTION 8. Exposure controls/personal protection. .../>>

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 137). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance		viscous liquid	
Colour		transparent	
Odour		odourless	
Odour threshold.		Not available.	
pH.		8 -9	
Melting point / freezing point.		Not available.	
Initial boiling point.	>	100 °C.	
Boiling range.		Not available.	
Flash point.		60 < T ≤ 93	°C.
Evaporation Rate		Not available.	
Flammability of solids and gases		Not available.	
Lower inflammability limit.		Not available.	
Upper inflammability limit.		Not available.	
Lower explosive limit.		Not available.	
Upper explosive limit.		Not available.	
Vapour pressure.		Not available.	
Vapour density		Not available.	
Relative density.		1,02-1,06	g/ml
Solubility		soluble in water	
Partition coefficient: n-octanol/water		Not available.	
Auto-ignition temperature.		Not available.	
Decomposition temperature.		Not available.	
Viscosity		Not available.	
Explosive properties		not applicable	
Oxidising properties		not applicable	
9.2. Other information.			

Information not available.

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL: decomposes in the presence of heat.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

2-BUTOXYETHANOL: can react dangerously with: aluminium, oxidising agents. Forms peroxide with air.



WATER BASED FLOOR PRIMER

Revision nr.2 Dated 26/02/2015 Printed on 16/11/2015 Page n. 5 / 7 ΕN

SECTION 10. Stability and reactivity. .../>>

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

2-BUTOXYETHANOL: avoid exposure to sources of heat and naked flames.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

2-BUTOXYETHANOL: hydrogen.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product contains sensitizing substance/s and may cause allergic reactions.

2-BUTOXYETHANOL LD50 (Oral). LD50 (Dermal). LC50 (Inhalation).

615 mg/kg Rat 405 mg/kg Rabbit 2,2 mg/l/4h Rat

SECTION 12. Ecological information.

12.1. Toxicity.

Information not available.

12.2. Persistence and degradability.

2-BUTOXYETHANOL Rapidly biodegradable.

12.3. Bioaccumulative potential.

2-BUTOXYETHANOL Partition coefficient: n-octanol/water. 0,81

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Neat product residues should be considered special non-hazardous waste. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

Not applicable.



WATER BASED FLOOR PRIMER

SECTION 14. Transport information. .../>>

14.2. UN proper shipping name.

Not applicable.

14.3. Transport hazard class(es).

Not applicable.

14.4. Packing group.

Not applicable.

14.5. Environmental hazards.

Not applicable.

14.6. Special precautions for user.

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006. None.

Substances in Candidate List (Art. 59 REACH).

None. Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012: None.

None.

Substances subject to the Rotterdam Convention: None.

Substances subject to the Stockholm Convention: None.

Healthcare controls. Information not available.

<u>VOC (Directive 2004/42/EC) :</u> One-pack performance coatings. VOC given in g/litre of product in a ready-to-use condition : Limit value: VOC of product :

140,00 (2010) 135,00

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4	Acute toxicity, category 4
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H319	Causes serious eye irritation.



WATER BASED FLOOR PRIMER

Revision nr.2 Dated 26/02/2015 Printed on 16/11/2015 Page n. 7 / 7

SECTION 16. Other information. .../>>

H315	Causes skin irritation.
EUH210	Safety data sheet available on request.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R20/21/22	HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.
R36/38	IRRITATING TO EYES AND SKIN.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 5. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EU) 453/2010 of the European Parliament
- 7. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 8. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 9. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 10. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 11. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.