

GRANIKOT ACRYLIC

Revision nr.6 Dated 29/06/2020 Printed on 31/08/2020 Page n. 1/9

Replaced revision:5 (Dated 22/04/2019)

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name GRANIKOT ACRYLIC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Acrylic plaster

1.3. Details of the supplier of the safety data sheet

Name VITEX S.A. Full address IMEROS TOPOS

District and Country 19300 ASPROPYRGOS (ATTIKI)

GREECE

Tel. (0030) 2105589400 Fax (0030) 2105597859

e-mail address of the competent person

responsible for the Safety Data Sheet vitexlab@vitex.gr

Product distribution by: VITEX S.A

1.4. Emergency telephone number

For urgent inquiries refer to (0030) 2105589400

(0030) 2107793777

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2015/830.

Hazard classification and indication: --

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

Signal words: --

Hazard statements:

EUH210 Safety data sheet available on request.

EUH208 Contains: 5-Chloro-2-methyl- 3(2H)-isothiazolone mixture with 2-Methyl- 3(2H)-isothiazolone (3:1)

2-methyl-2H-isothiazol-3-one

1,2-benziosothiazolin-3-one

May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements:

P102 Keep out of reach of children.
P273 Avoid release to the environment.

P301+P312 IF SWALLOWED: Call a POISON CENTER / doctor / . . . / if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice / attention.

VOC (Directive 2004/42/EC):

Coatings for exterior walls of mineral substrate.

VOC given in g/litre of product in a ready-to-use condition : 39,00



GRANIKOT ACRYLIC

Revision nr.6 Dated 29/06/2020 Printed on 31/08/2020 Page n. 2 / 9

Replaced revision:5 (Dated 22/04/2019)

SECTION 2. Hazards identification .../>>

Limit value: 40,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

1,2-benziosothiazolin-3-one

CAS 2634-33-5 0,03 ≤ x < 0,05 Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Dam. 1 H318, Skin Irrit. 2 H315,

Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1

EC 220-120-9 INDEX 613-088-00-6

INDEX 013-000-00-0

5-Chloro-2-methyl- 3(2H)-isothiazolone mixture with 2-Methyl- 3(2H)-isothiazolone (3:1)

CAS 55965-84-9 $0 \le x < 0,0015$ Acute Tox. 3 H301+H311+H331, Skin Corr. 1B H314, Eye Dam. 1 H318,

Skin Sens. 1 H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100

EC

INDEX 613-167-00-5 **2-methyl-2H-isothiazol-3-one**

CAS 2682-20-4 0 ≤ x < 0.0015 Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1B H314,

Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=10,

Aquatic Chronic 1 H410 M=1, EUH071

EC 220-239-6

INDEX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.



GRANIKOT ACRYLIC

Revision nr.6 Dated 29/06/2020 Printed on 31/08/2020 Page n. 3 / 9

Replaced revision:5 (Dated 22/04/2019)

SECTION 5. Firefighting measures .../>>

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Information not available

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body



GRANIKOT ACRYLIC

Revision nr.6 Dated 29/06/2020 Printed on 31/08/2020 Page n. 4 / 9 Replaced revision:5 (Dated 22/04/2019)

SECTION 8. Exposure controls/personal protection .../>

with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Value Appearance viscous liquid Colour white Odour odourless Odour threshold Not available 8-9 Melting point / freezing point Not available Initial boiling point 100 °C Boiling range Not available Flash point 93 °C **Evaporation Rate** Not available Flammability of solids and gases Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available Vapour pressure Not available Vapour density Not available Relative density 1.85-1.95 a/ml Solubility soluble in water Partition coefficient: n-octanol/water Not available Auto-ignition temperature Not available Not available Decomposition temperature Viscosity 25000-30000 cps Explosive properties Not available Oxidising properties Not available

Information

9.2. Other information

VOC (Directive 2010/75/EC):

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.



GRANIKOT ACRYLIC

Revision nr.6 Dated 29/06/2020 Printed on 31/08/2020 Page n. 5 / 9

Replaced revision:5 (Dated 22/04/2019)

SECTION 10. Stability and reactivity .../>

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

LD50 (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

1,2-benziosothiazolin-3-one

 $LD50 \ (Oral) \\ LD50 \ (Dermal) \\ > 2,175 \ mg/kg \ 1,2-benziosothiazolin-3-one \\ > 1,221 \ mg/kg \ 1,2-benziosothiazolin-3-one$

LC50 (Inhalation) 0,5 mg/l

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

5-Chloro-2-methyl- 3(2H)-isothiazolone mixture with 2-Methyl- 3(2H)-isothiazolone (3:1)

2-methyl-2H-isothiazol-3-one

1,2-benziosothiazolin-3-one

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY



VITEX S.A. **GRANIKOT ACRYLIC**

Revision nr 6 Dated 29/06/2020 Printed on 31/08/2020 Page n. 6 / 9

Replaced revision:5 (Dated 22/04/2019)

SECTION 11. Toxicological information .../>>

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: 25000-30000 cps

SECTION 12. Ecological information

12.1. Toxicity

1,2-benziosothiazolin-3-one

LC50 - for Fish > 2,18 mg/l/96h 1,2-benziosothiazolin-3-one Oncorhynchus mykiss OECD Test Guideline

203

EC50 - for Crustacea > 2,94 mg/l/48h 1,2-benziosothiazolin-3-one Daphnia magna OECD Test Guideline 202 EC50 - for Algae / Aquatic Plants

> 0,11 mg/l/72h 1,2-benziosothiazolin-3-one Pseudokirchneriella subcapitata OECD Test

Guideline 201

5-Chloro-2-methyl- 3(2H)-isothiazolone mixture with 2-Methyl- 3(2H)-isothiazolone (3:1)

EC50 - for Crustacea > 0,018 mg/l/48h

Chronic NOEC for Fish 0,5 mg/l

12.2. Persistence and degradability

Information not available

12.3. Bioaccumulative potential

2-methyl-2H-isothiazol-3-one

Partition coefficient: n-octanol/water 0,32 Log Kow

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.



VITEX S.A. GRANIKOT ACRYLIC

Revision nr.6 Dated 29/06/2020 Printed on 31/08/2020 Page n. 7 / 9 Replaced revision:5 (Dated 22/04/2019)

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls
Information not available

VOC (Directive 2004/42/EC):

Coatings for exterior walls of mineral substrate.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.



GRANIKOT ACRYLIC

Revision nr 6 Dated 29/06/2020 Printed on 31/08/2020

Replaced revision:5 (Dated 22/04/2019)

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute toxicity, category 2 Acute Tox. 2 Acute Tox. 3 Acute toxicity, category 3 Acute Tox. 4 Acute toxicity, category 4 Skin corrosion, category 1B Skin Corr. 1B Serious eye damage, category 1 Eye Dam. 1 Skin Irrit. 2 Skin irritation, category 2 Skin Sens. 1 Skin sensitization, category 1 Skin Sens. 1A Skin sensitization, category 1A

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1 **Aquatic Chronic 1** Hazardous to the aquatic environment, chronic toxicity, category 1

Fatal if inhaled. H330

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

Toxic if swallowed H301 H311 Toxic in contact with skin. H302 Harmful if swallowed. H332 Harmful if inhaled.

Causes severe skin burns and eye damage. H314

H318 Causes serious eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

Very toxic to aquatic life. H400

H410 Very toxic to aquatic life with long lasting effects.

Corrosive to the respiratory tract. **EUH071 EUH210** Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament



GRANIKOT ACRYLIC

Revision nr.6 Dated 29/06/2020 Printed on 31/08/2020 Page n. 9 / 9 Replaced revision:5 (Dated 22/04/2019)

SECTION 16. Other information .../>>

- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- FCHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 11 / 12 / 15.