

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: DUCO 748 (Product Code 114748)

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: High performance coatings for wood, metal

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Berling S.A. Thesi Agia Paraskevi 32011 Inofyta Viotias - Greece Phone.: +302262031663 - Fax: +302262031293 info@berling.gr www.berling.gr

1.4 Emergency telephone number: +30 210 7793 777 (Greek Poison Info Center)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411 Flam. Liq. 3: Flammable liquids, Category 3, H226 STOT RE 2: Specific target organ toxicity, repeated exposure, Category 2, H373 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Flam. Liq. 3: H226 - Flammable liquid and vapour STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure STOT SE 3: H336 - May cause drowsiness or dizziness

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand
P102: Keep out of reach of children
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P280: Wear protective gloves/protective clothing/eye protection/face protection
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
P403+P233: Store in a well-ventilated place. Keep container tightly closed
P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking EUH208: Contains 2-Propenoic acid, 2-methyl-, 2-(dimethylamino)ethyl ester, polymer with butyl 2-propenoate, comps. with polyethylene glycol hydrogen maleate C9-11-alkyl ethers, Butanone oxime, Cobalt bis(2-ethylhexanoate). May produce an allergic reaction

Substances that contribute to the classification

naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7 (CAS: 64742-82-1); Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (CAS: 64742-82-1)

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

** Changes with regards to the previous version



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives, fillers, pigments and resins in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification		Chemical name/Classification		Concentration
CAS: 64742-82-1	naphtha (petroleum),	, hydrodesulphurized heavy , < 0.1 % EC 200-753-7(1)	ATP ATP05	
EC: 265-185-4 Index: 649-330-00-2 REACH 01-2119490979-12-	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger	() () () ()	9,9 - <19 %
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH 01-2119488216-32- · XXXX	Xylene ⁽¹⁾ Regulation 1272/2008	Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	ATP CLP00	4,9 - <9,9 %
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH 01-2119475791-29-	2-methoxy-1-methyle Regulation 1272/2008	ethyl acetate ⁽²⁾ Flam. Liq. 3: H226 - Warning	ATP ATP01	2,4 - <4,9 %
CAS: 64742-82-1	Hydrocarbons, C9-C1	2, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ⁽¹⁾	Self-classified	
EC: 919-446-0 Index: Non-applicable REACH 01-2119458049-33-	k: Non-applicable Regulation 1272/2008 Aquate Chronic 2: PH17, Asp. Tox. 1: P304; Plaint. Liq. 3: P1226; STOT KE 1: H370; STOT KE 3: H336; EILHG6 - Danger			
CAS: 7779-90-0	trizinc bis(orthophos	phate) ⁽¹⁾	ATP CLP00	
EC: 231-944-3 Index: Non-applicable REACH 01-2119485044-40-	dex: Non-applicable ACH 01-2119485044-40-			
CAS: 112-07-2	2-butoxyethyl acetate	B(2)	Self-classified	
EC: 203-933-3 Index: 607-038-00-2 REACH 01-2119475112-47-	index: 607-038-00-2 REQUIATION 1272/2008 Acute Tox. 4: H302+H312+H332 - Warning			0,9 - <2,4 %
CAS: 1259547-09-5		nethyl-, 2-(dimethylamino)ethyl ester, polymer with butyl 2-	Self-classified	
EC: Non-applicable Index: Non-applicable REACH Non-applicable :	propenoate, comps. v Regulation 1272/2008	vith polyethylene glycol hydrogen maleate C9-11-alkyl ethers ⁽¹⁾ Skin Sens. 1: H317 - Warning	٩	0,24 - <0,9 %
CAS: 107-98-2	1-methoxy-2-propan	D ⁽²⁾	ATP ATP01	
EC: 203-539-1 Index: 603-064-00-3 REACH 01-2119457435-35-	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	۵)	0,24 - <0,9 %
CAS: 96-29-7	Butanone oxime ⁽¹⁾		ATP CLP00	
EC: 202-496-6 Index: 616-014-00-0 REACH 01-2119539477-28-	Regulation 1272/2008	Acute Tox. 4: H312; Carc. 2: H351; Eye Dam. 1: H318; Skin Sens. 1: H317 - Danger	104	0,24 - <0,9 %
CAS: 22464-99-9	2-ethylhexanoic acid,	zirconium salt ⁽¹⁾	Self-classified	
EC: 245-018-1 Index: Non-applicable REACH 01-2119979088-21-	Regulation 1272/2008	Repr. 2: H361d - Warning	\$	0,24 - <0,9 %
CAS: 136-51-6	calcium bis(2-ethylhe	exanoate) ⁽¹⁾	Self-classified	
EC: 205-249-0 Index: Non-applicable REACH 01-2119978297-19-	Regulation 1272/2008	Eye Dam. 1: H318; Repr. 2: H361d - Danger	۵.	0,24 - <0,9 %
CAS: 136-52-7	Cobalt bis(2-ethylhex	anoate) ⁽¹⁾	Self-classified	
EC: 205-250-6 Index: Non-applicable REACH 01-2119524678-29-	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Chronic 1: H410; Repr. 2: H361f; Skin Sens. 1: H3 Warning	17 -	0,09 - <0,24 %
CAS: 1330-20-7	Xylene ⁽²⁾		Self-classified	
EC: 215-535-7 Index: 601-022-00-9 REACH 01-2119488216-32-	Regulation 1272/2008	Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	104	<0,09 %
CAS: 100-41-4	Ethylbenzene ⁽²⁾		ATP ATP06	
EC: 202-849-4 Index: 601-023-00-4 REACH 01-2119489370-35-	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	104	<0,09 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830 ⁽²⁾ Substance with a Union workplace exposure limit

** Changes with regards to the previous version



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

Identification		Chemical name/Classification		Concentration
CAS: 112-34-5	2-(2-butoxyethoxy)e	thanol ⁽²⁾	ATP CLP00	
EC: 203-961-6 Index: 603-096-00-8 REACH 01-2119475104-44-	Regulation 1272/2008	Eye Irrit. 2: H319 - Warning	\langle	<0,09 %
CAS: 108-88-3	Toluene ⁽²⁾		ATP CLP00	
EC: 203-625-9 Index: 601-021-00-3 REACH 01-2119471310-51-	Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	() (♦) (♦)	< 0,09 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830 ⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

Indication of any immediate medical attention and special treatment needed:

Non-applicable

4.3

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:



SECTION 5: FIREFIGHTING MEASURES (continued)

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

- C.- Technical recommendations to prevent ergonomic and toxicological risks
 - Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.
- D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:5 °CMaximum Temp.:35 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification		Environmental lim	its
Xylene	IOELV (8h)	50 ppm	221 mg/m ³
CAS: 1330-20-7	IOELV (STEL)	100 ppm	442 mg/m ³
EC: 215-535-7	Year	2018	
Ethylbenzene	IOELV (8h)	100 ppm	442 mg/m ³
CAS: 100-41-4	IOELV (STEL)	200 ppm	884 mg/m ³
EC: 202-849-4	Year	2018	
Toluene	IOELV (8h)	50 ppm	192 mg/m ³
CAS: 108-88-3	IOELV (STEL)	100 ppm	384 mg/m ³
EC: 203-625-9	Year	2018	
Xylene	IOELV (8h)	50 ppm	221 mg/m ³
CAS: 1330-20-7	IOELV (STEL)	100 ppm	442 mg/m ³
EC: 215-535-7	Year	2018	
1-methoxy-2-propanol	IOELV (8h)	100 ppm	375 mg/m ³
CAS: 107-98-2	IOELV (STEL)	150 ppm	563 mg/m ³
EC: 203-539-1	Year	2018	
2-(2-butoxyethoxy)ethanol	IOELV (8h)	10 ppm	67.5 mg/m ³
CAS: 112-34-5	IOELV (STEL)	15 ppm	101.2 mg/m ³
EC: 203-961-6	Year	2018	
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m ³
CAS: 108-65-6	IOELV (STEL)	100 ppm	550 mg/m ³
EC: 203-603-9	Year	2018	-
2-butoxyethyl acetate	IOELV (8h)	20 ppm	133 mg/m ³
CAS: 112-07-2	IOELV (STEL)	50 ppm	333 mg/m ³
EC: 203-933-3	Year	2018	

DNEL (Workers):

		Short	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable	
EC: 215-535-7	Inhalation	289 mg/m ³	289 mg/m ³	77 mg/m ³	Non-applicable	
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	153,5 mg/kg	Non-applicable	
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	275 mg/m ³	Non-applicable	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 64742-82-1	Dermal	Non-applicable	Non-applicable	44 mg/kg	Non-applicable	
EC: 919-446-0	Inhalation	Non-applicable	Non-applicable	330 mg/m ³	Non-applicable	
trizinc bis(orthophosphate)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 7779-90-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable	
EC: 231-944-3	Inhalation	Non-applicable	Non-applicable	5 mg/m ³	Non-applicable	
2-butoxyethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 112-07-2	Dermal	102 mg/kg	Non-applicable	102 mg/kg	Non-applicable	
EC: 203-933-3	Inhalation	775 mg/m ³	333 mg/m ³	133 mg/m ³	Non-applicable	
1-methoxy-2-propanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 107-98-2	Dermal	Non-applicable	Non-applicable	50,6 mg/kg	Non-applicable	
EC: 203-539-1	Inhalation	Non-applicable	553,5 mg/m ³	369 mg/m ³	Non-applicable	
Butanone oxime	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 96-29-7	Dermal	2,5 mg/kg	Non-applicable	1,3 mg/kg	Non-applicable	
EC: 202-496-6	Inhalation	Non-applicable	Non-applicable	9 mg/m ³	3,33 mg/m ³	
2-ethylhexanoic acid, zirconium salt	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 22464-99-9	Dermal	Non-applicable	Non-applicable	15,75 mg/kg	Non-applicable	
EC: 245-018-1	Inhalation	Non-applicable	Non-applicable	5 mg/m ³	Non-applicable	
calcium bis(2-ethylhexanoate)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 136-51-6	Dermal	Non-applicable	Non-applicable	5,67 mg/kg	Non-applicable	
EC: 205-249-0	Inhalation	Non-applicable	Non-applicable	39,98 mg/m ³	Non-applicable	



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Cobalt bis(2-ethylhexanoate)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 136-52-7	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 205-250-6	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,2351 mg/m ³
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	289 mg/m ³	289 mg/m ³	77 mg/m ³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
2-(2-butoxyethoxy)ethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 112-34-5	Dermal	Non-applicable	Non-applicable	20 mg/kg	Non-applicable
EC: 203-961-6	Inhalation	Non-applicable	101,2 mg/m ³	67,5 mg/m ³	67,5 mg/m ³
Toluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	384 mg/m ³	384 mg/m ³	192 mg/m ³	192 mg/m ³

DNEL (General population):

		Short	exposure	Long	Long exposure	
Identification		Systemic	Local	Systemic	Local	
Xylene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable	
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable	
EC: 215-535-7	Inhalation	Non-applicable	Non-applicable	14,8 mg/m ³	Non-applicable	
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	1,67 mg/kg	Non-applicable	
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	54,8 mg/kg	Non-applicable	
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	Non-applicable	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Oral	Non-applicable	Non-applicable	26 mg/kg	Non-applicable	
CAS: 64742-82-1	Dermal	Non-applicable	Non-applicable	26 mg/kg	Non-applicable	
EC: 919-446-0	Inhalation	Non-applicable	Non-applicable	71 mg/m ³	Non-applicable	
trizinc bis(orthophosphate)	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable	
CAS: 7779-90-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable	
EC: 231-944-3	Inhalation	Non-applicable	Non-applicable	2,5 mg/m ³	Non-applicable	
2-butoxyethyl acetate	Oral	18 mg/kg	Non-applicable	4,3 mg/kg	Non-applicable	
CAS: 112-07-2	Dermal	27 mg/kg	Non-applicable	36 mg/kg	Non-applicable	
EC: 203-933-3	Inhalation	499 mg/m ³	166 mg/m ³	67 mg/m ³	Non-applicable	
1-methoxy-2-propanol	Oral	Non-applicable	Non-applicable	3,3 mg/kg	Non-applicable	
CAS: 107-98-2	Dermal	Non-applicable	Non-applicable	18,1 mg/kg	Non-applicable	
EC: 203-539-1	Inhalation	Non-applicable	Non-applicable	43,9 mg/m ³	Non-applicable	
Butanone oxime	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 96-29-7	Dermal	1,5 mg/kg	Non-applicable	0,78 mg/kg	Non-applicable	
EC: 202-496-6	Inhalation	Non-applicable	Non-applicable	2,7 mg/m ³	2 mg/m ³	
2-ethylhexanoic acid, zirconium salt	Oral	Non-applicable	Non-applicable	7,9 mg/kg	Non-applicable	
CAS: 22464-99-9	Dermal	Non-applicable	Non-applicable	7,9 mg/kg	Non-applicable	
EC: 245-018-1	Inhalation	Non-applicable	Non-applicable	2,5 mg/m ³	Non-applicable	
calcium bis(2-ethylhexanoate)	Oral	Non-applicable	Non-applicable	2,83 mg/kg	Non-applicable	
CAS: 136-51-6	Dermal	Non-applicable	Non-applicable	2,83 mg/kg	Non-applicable	
EC: 205-249-0	Inhalation	Non-applicable	Non-applicable	9,86 mg/m ³	Non-applicable	
Cobalt bis(2-ethylhexanoate)	Oral	Non-applicable	Non-applicable	0,0558 mg/kg	Non-applicable	
CAS: 136-52-7	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
EC: 205-250-6	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,037 mg/m ³	
Xylene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable	
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable	
EC: 215-535-7	Inhalation	Non-applicable	Non-applicable	14,8 mg/m ³	Non-applicable	



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

		Short	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable	
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable	
2-(2-butoxyethoxy)ethanol	Oral	Non-applicable	Non-applicable	1,25 mg/kg	Non-applicable	
CAS: 112-34-5	Dermal	Non-applicable	Non-applicable	10 mg/kg	Non-applicable	
EC: 203-961-6	Inhalation	Non-applicable	50,6 mg/m ³	34 mg/m ³	34 mg/m ³	
Toluene	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable	
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable	
EC: 203-625-9	Inhalation	226 mg/m ³	226 mg/m ³	56,5 mg/m ³	56,5 mg/m ³	
PNEC:						
Identification						
Xylene	STP	6,58 mg/L	Fresh water		0,327 mg/L	
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water		0,327 mg/L	
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh	water)	12,46 mg/kg	
	Oral	Non-applicable	Sediment (Marine		12,46 mg/kg	
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water		0,635 mg/L	
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water		0,0635 mg/L	
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh	water)	3,29 mg/kg	
20. 205 005 5	Oral	Non-applicable	Sediment (Marine		0,329 mg/kg	
trizinc bis(orthophosphate)	STP	0,1 mg/L	Fresh water	,	0,0206 mg/L	
CAS: 7779-90-0	Soil	35,6 mg/kg	Marine water		0,0200 mg/L	
EC: 231-944-3	Intermittent	Non-applicable	Sediment (Fresh	water)	117,8 mg/kg	
	Oral	Non-applicable	Sediment (Marine		56,5 mg/kg	
2-butoxyethyl acetate	STP	90 mg/L	Fresh water	,	0,304 mg/L	
CAS: 112-07-2	Soil	0,68 mg/kg	Marine water		0,0304 mg/L	
EC: 203-933-3	Intermittent	0,56 mg/L	Sediment (Fresh	water)	2,03 mg/kg	
	Oral	60 g/kg	Sediment (Marine		0,203 mg/kg	
1-methoxy-2-propanol	STP	100 mg/L	Fresh water	,	10 mg/L	
CAS: 107-98-2	Soil	5,49 mg/kg	Marine water		1 mg/L	
EC: 203-539-1	Intermittent	100 mg/L	Sediment (Fresh	water)	52,3 mg/kg	
	Oral	Non-applicable	Sediment (Marine		5,2 mg/kg	
Butanone oxime	STP	177 mg/L	Fresh water		0,256 mg/L	
CAS: 96-29-7	Soil	Non-applicable	Marine water		Non-applicable	
EC: 202-496-6	Intermittent	0,118 mg/L	Sediment (Fresh	water)	Non-applicable	
	Oral	Non-applicable	Sediment (Marine		Non-applicable	
2-ethylhexanoic acid, zirconium salt	STP	71,7 mg/L	Fresh water		0,36 mg/L	
CAS: 22464-99-9	Soil	1,06 mg/kg	Marine water		0,036 mg/L	
EC: 245-018-1	Intermittent	0,493 mg/L	Sediment (Fresh	water)	6,37 mg/kg	
	Oral	Non-applicable	Sediment (Marine	· ·	0,637 mg/kg	
calcium bis(2-ethylhexanoate)	STP	71,7 mg/L	Fresh water		0,36 mg/L	
CAS: 136-51-6	Soil	1,06 mg/kg	Marine water		0,036 mg/L	
EC: 205-249-0	Intermittent	0,493 mg/L	Sediment (Fresh	water)	6,37 mg/kg	
	Oral	Non-applicable	Sediment (Marine	<u> </u>	0,637 mg/kg	
Cobalt bis(2-ethylhexanoate)	STP	0,37 mg/L	Fresh water		0,00051 mg/L	
CAS: 136-52-7	Soil	7,9 mg/kg	Marine water		0,00236 mg/L	
FC: 205-250-6	Intermittent	Non-applicable	Sediment (Fresh	water)	9,5 ma/ka	

EC: 205-250-6

CAS: 1330-20-7

EC: 215-535-7

Xylene

Oral

STP

Soil

Oral

Intermittent

Intermittent

- CONTINUED ON NEXT PAGE -

Non-applicable

Non-applicable

6,58 mg/L

2,31 mg/kg

0,327 mg/L

Non-applicable

Sediment (Fresh water)

Sediment (Marine water)

Sediment (Fresh water)

Sediment (Marine water)

-resh water

Marine water

9,5 mg/kg

9,5 mg/kg

0,327 mg/L

0,327 mg/L

12,46 mg/kg

12,46 mg/kg



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	1,37 mg/kg
2-(2-butoxyethoxy)ethanol	STP	200 mg/L	Fresh water	1 mg/L
CAS: 112-34-5	Soil	0,4 mg/kg	Marine water	0,1 mg/L
EC: 203-961-6	Intermittent	3,9 mg/L	Sediment (Fresh water)	4 mg/kg
	Oral	56 g/kg	Sediment (Marine water)	0,4 mg/kg
Toluene	STP	13,61 mg/L	Fresh water	0,68 mg/L
CAS: 108-88-3	Soil	2,89 mg/kg	Marine water	0,68 mg/L
EC: 203-625-9	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves		EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory fac protection	Face mask	CAT II	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6529:2005 EN ISO 13688:2013 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer 's instructions.



Pictogram		PPE	Labelling		CEN Standard		Remarks
Mandatory foot protection	against antistatio	twear for protection chemical risk, with and heat resistant properties		EN	EN 13287:2008 ISO 20345:2011 N 13832-1:2006	Replac	ce boots at any sign of deterioration
F Additional eme	gency meas	sures					
Emergency	neasure	SI	tandards		Emergency measur	e	Standards
	+		SI Z358-1 8864-1:2002		(◎ + T		DIN 12 899 ISO 3864-1:2002
Emergency	shower				Eyewash stations		
Environmental e	cposure co	ontrols:					
In accordance with	the commu	nity legislation fo	or the protection	n of the	environment it is re	commend	led to avoid environmental sp

With regard to Directive 2010/75/EU, this product has the following characteristics

V.O.C. (Supply):Not availableV.O.C. density at 25 °C:Not availableAverage carbon number:Not availableAverage molecular weight:118,24 g/molWith regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:V.O.C. density at 25 °C:500 kg/m³ (500 g/L)EU limit for the product (Cat. A.I):500 g/L (2010)Components:WHITE SPIRIT - 14 % v/v

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:	
Physical state at 20 °C:	Liquid
Appearance:	Not available
Colour:	According to the markings on the package
Odour:	Not available
Odour threshold:	Non-applicable *
Volatility:	
Boiling point at atmospheric pressure:	147 °C
Vapour pressure at 25 °C:	Non-applicable *
Vapour pressure at 50 °C:	Non-applicable *
Evaporation rate at 25 °C:	Non-applicable *
Product description:	
Density at 25 °C:	1110 - 1170 kg/m³
Relative density at 25 °C:	Non-applicable *
Dynamic viscosity at 25 °C:	1235,61 - 1129,77 cP
Kinematic viscosity at 25 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
*Not relevant due to the nature of the product, not providing \ensuremath{i}	nformation property of its hazards.



pH:	Non-applicable *	
Vapour density at 25 °C:	Non-applicable *	
Partition coefficient n-octanol/water 2	5 °C: Non-applicable *	
Solubility in water at 25 °C:	Non-applicable *	
Solubility properties:	Non-applicable *	
Decomposition temperature:	Non-applicable *	
Melting point/freezing point:	Non-applicable *	
Explosive properties:	Non-applicable *	
Oxidising properties:	Non-applicable *	
Flammability:		
Flash Point:	38 °C	
Flammability (solid, gas):	Non-applicable *	
Autoignition temperature:	204 °C	
Lower flammability limit:	Not available	
Upper flammability limit:	Not available	
Explosive:		
Lower explosive limit:	Non-applicable *	
Upper explosive limit:	Non-applicable *	
Other information:		
Surface tension at 25 °C:	Non-applicable *	
Refraction index:	Non-applicable *	
*Not relevant due to the nature of the product	t, not providing information property of its hazards.	

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.

- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.

- Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous
 - system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
 - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	A	Acute toxicity		
Xylene	LD50 oral	2100 mg/kg	Rat	
CAS: 1330-20-7	LD50 dermal	1100 mg/kg (ATEi)	Rat	
EC: 215-535-7	LC50 inhalation	11 mg/L (4 h) (ATEi)		
naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7	LD50 oral	5100 mg/kg	Rat	
CAS: 64742-82-1	LD50 dermal	3160 mg/kg	Rabbit	
EC: 265-185-4	LC50 inhalation	12 mg/L (4 h)	Rat	



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification		Acute toxicity	Genus
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	LD50 oral	>2000 mg/kg	
CAS: 64742-82-1	LD50 dermal	>2000 mg/kg	
EC: 919-446-0	LC50 inhalation	>20 mg/L (4 h)	
trizinc bis(orthophosphate)	LD50 oral	>2000 mg/kg	
CAS: 7779-90-0	LD50 dermal	>2000 mg/kg	
EC: 231-944-3	LC50 inhalation	>5 mg/L (4 h)	
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	5100 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
2-butoxyethyl acetate	LD50 oral	1880 mg/kg	Rat
CAS: 112-07-2	LD50 dermal	1500 mg/kg	Rabbit
EC: 203-933-3	LC50 inhalation	>20 mg/L	
2-Propenoic acid, 2-methyl-, 2-(dimethylamino)ethyl ester, polymer with butyl 2- propenoate, comps. with polyethylene glycol hydrogen maleate C9-11-alkyl ethers	LD50 oral	>2000 mg/kg	
CAS: 1259547-09-5	LD50 dermal	>2000 mg/kg	
EC: Non-applicable	LC50 inhalation	Non-applicable	
1-methoxy-2-propanol	LD50 oral	>2000 mg/kg	
CAS: 107-98-2	LD50 dermal	>2000 mg/kg	
EC: 203-539-1	LC50 inhalation	>20 mg/L	
Butanone oxime	LD50 oral	2100 mg/kg	Rat
CAS: 96-29-7	LD50 dermal	1100 mg/kg	Rat
EC: 202-496-6	LC50 inhalation	>20 mg/L	
2-ethylhexanoic acid, zirconium salt	LD50 oral	2043 mg/kg	Rat
CAS: 22464-99-9	LD50 dermal	>2000 mg/kg	
EC: 245-018-1	LC50 inhalation	>5 mg/L	
calcium bis(2-ethylhexanoate)	LD50 oral	2043 mg/kg	Rat
CAS: 136-51-6	LD50 dermal	>2000 mg/kg	
EC: 205-249-0	LC50 inhalation	>5 mg/L	
Cobalt bis(2-ethylhexanoate)	LD50 oral	>2000 mg/kg	
CAS: 136-52-7	LD50 dermal	>2000 mg/kg	
EC: 205-250-6	LC50 inhalation	>5 mg/L	
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg	Rat
EC: 215-535-7	LC50 inhalation	>20 mg/L	
Ethylbenzene	LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4	LD50 dermal	15354 mg/kg	Rabbit
EC: 202-849-4	LC50 inhalation	17,2 mg/L (4 h)	Rat
2-(2-butoxyethoxy)ethanol	LD50 oral	>2000 mg/kg	
CAS: 112-34-5	LD50 dermal	>2000 mg/kg	
EC: 203-961-6	LC50 inhalation	>20 mg/L	
Toluene	LD50 oral	5580 mg/kg	Rat
CAS: 108-88-3	LD50 dermal	12124 mg/kg	Rat
EC: 203-625-9	LC50 inhalation	28,1 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7	LC50	Non-applicable		
CAS: 64742-82-1	EC50	4.3 mg/L (96 h)	Crangon crangon	Crustacean
EC: 265-185-4	EC50	Non-applicable		



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Species	Genus
Xylene	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 1330-20-7	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacear
EC: 215-535-7	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacear
EC: 203-603-9	EC50	Non-applicable		
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	LC50	1 - 10 mg/L (96 h)		Fish
CAS: 64742-82-1	EC50	1 - 10 mg/L		Crustacear
EC: 919-446-0	EC50	1 - 10 mg/L		Algae
trizinc bis(orthophosphate)	LC50	0.1 - 1 mg/L (96 h)		Fish
CAS: 7779-90-0	EC50	0.1 - 1 mg/L		Crustacear
EC: 231-944-3	EC50	0.1 - 1 mg/L		Algae
1-methoxy-2-propanol	LC50	20800 mg/L (96 h)	Pimephales promelas	Fish
CAS: 107-98-2	EC50	23300 mg/L (48 h)	Daphnia magna	Crustacear
EC: 203-539-1	EC50	1000 mg/L (168 h)	Selenastrum capricornutum	Algae
Butanone oxime	LC50	843 mg/L (96 h)	Pimephales promelas	Fish
CAS: 96-29-7	EC50	750 mg/L (48 h)	Daphnia magna	Crustacear
EC: 202-496-6	EC50	83 mg/L (72 h)	Scenedesmus subspicatus	Algae
calcium bis(2-ethylhexanoate)	LC50	270 mg/L (96 h)	N/A	Fish
CAS: 136-51-6	EC50	Non-applicable		
EC: 205-249-0	EC50	Non-applicable		
Cobalt bis(2-ethylhexanoate)	LC50	0.1 - 1 mg/L (96 h)		Fish
CAS: 136-52-7	EC50	0.1 - 1 mg/L		Crustacear
EC: 205-250-6	EC50	0.1 - 1 mg/L		Algae
Xylene	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 1330-20-7	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacear
EC: 215-535-7	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
Ethylbenzene	LC50	42.3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacear
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
2-(2-butoxyethoxy)ethanol	LC50	1300 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 112-34-5	EC50	2850 mg/L (24 h)	Daphnia magna	Crustacear
EC: 203-961-6	EC50	53 mg/L (192 h)	Microcystis aeruginosa	Algae
Toluene	LC50	13 mg/L (96 h)	Carassius auratus	Fish
CAS: 108-88-3	EC50	11.5 mg/L (48 h)	Daphnia magna	Crustacear
EC: 203-625-9	EC50	125 mg/L (48 h)	Scenedesmus subspicatus	Algae

12.2 Persistence and degradability:

Identification	Degra	adability	Biodegradab	ility
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
2-butoxyethyl acetate	BOD5	Non-applicable	Concentration	30 mg/L
CAS: 112-07-2	COD	Non-applicable	Period	28 days
EC: 203-933-3	BOD5/COD	0.51	% Biodegradable	77,3 %
1-methoxy-2-propanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 107-98-2	COD	Non-applicable	Period	28 days
EC: 203-539-1	BOD5/COD	Non-applicable	% Biodegradable	90 %
Butanone oxime	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 96-29-7	COD	Non-applicable	Period	28 days
EC: 202-496-6	BOD5/COD	Non-applicable	% Biodegradable	24 %



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	D	egradability	Biod	egradability
2-ethylhexanoic acid, zirconium salt	BOD5	Non-applicable	Concentration	20 mg/L
CAS: 22464-99-9	COD	Non-applicable	Period	28 days
EC: 245-018-1	BOD5/COD	Non-applicable	% Biodegradable	99 %
calcium bis(2-ethylhexanoate)	BOD5	Non-applicable	Concentration	20 mg/L
CAS: 136-51-6	COD	Non-applicable	Period	28 days
EC: 205-249-0	BOD5/COD	Non-applicable	% Biodegradable	99 %
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
2-(2-butoxyethoxy)ethanol	BOD5	0.25 g O2/g	Concentration	100 mg/L
CAS: 112-34-5	COD	2.08 g O2/g	Period	28 days
EC: 203-961-6	BOD5/COD	0.12	% Biodegradable	92 %
Foluene	BOD5	2.5 g O2/g	Concentration	100 mg/L
CAS: 108-88-3	COD	Non-applicable	Period	14 days
EC: 203-625-9	BOD5/COD	Non-applicable	% Biodegradable	100 %

12.3 Bioaccumulative potential:

Identification	Bioaccur	mulation potential
naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7	BCF	645
CAS: 64742-82-1	Pow Log	4
EC: 265-185-4	Potential	High
Xylene	BCF	9
CAS: 1330-20-7	Pow Log	2.77
EC: 215-535-7	Potential	Low
2-methoxy-1-methylethyl acetate	BCF	1
CAS: 108-65-6	Pow Log	0.43
EC: 203-603-9	Potential	Low
2-butoxyethyl acetate	BCF	3
CAS: 112-07-2	Pow Log	1.51
EC: 203-933-3	Potential	Low
1-methoxy-2-propanol	BCF	3
CAS: 107-98-2	Pow Log	-0.44
EC: 203-539-1	Potential	Low
Butanone oxime	BCF	5
CAS: 96-29-7	Pow Log	0.59
EC: 202-496-6	Potential	Low
2-ethylhexanoic acid, zirconium salt	BCF	
CAS: 22464-99-9	Pow Log	2.96
EC: 245-018-1	Potential	
calcium bis(2-ethylhexanoate)	BCF	
CAS: 136-51-6	Pow Log	2.96
EC: 205-249-0	Potential	
Xylene	BCF	9
CAS: 1330-20-7	Pow Log	2.77
EC: 215-535-7	Potential	Low
Ethylbenzene	BCF	1
CAS: 100-41-4	Pow Log	3.15
EC: 202-849-4	Potential	Low
2-(2-butoxyethoxy)ethanol	BCF	0.46
CAS: 112-34-5	Pow Log	0.56
EC: 203-961-6	Potential	Low



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification		Bioaccumulation potential	
Toluene		BCF	13
CAS: 108-88-3		Pow Log	2.73
EC: 203-625-9		Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Xylene	Кос	202	Henry	524,86 Pa·m³/mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes
2-butoxyethyl acetate	Кос	Non-applicable	Henry	5,532E-1 Pa·m³/mc
CAS: 112-07-2	Conclusion	Non-applicable	Dry soil	No
EC: 203-933-3	Surface tension	Non-applicable	Moist soil	Yes
Butanone oxime	Кос	3	Henry	Non-applicable
CAS: 96-29-7	Conclusion	Very High	Dry soil	Non-applicable
EC: 202-496-6	Surface tension	2,57E-2 N/m (25 °C)	Moist soil	Non-applicable
2-ethylhexanoic acid, zirconium salt	Кос	Non-applicable	Henry	2,94E-1 Pa·m ³ /mol
CAS: 22464-99-9	Conclusion	Non-applicable	Dry soil	Yes
EC: 245-018-1	Surface tension	Non-applicable	Moist soil	Yes
calcium bis(2-ethylhexanoate)	Кос	Non-applicable	Henry	2,94E-1 Pa·m ³ /mol
CAS: 136-51-6	Conclusion	Non-applicable	Dry soil	Yes
EC: 205-249-0	Surface tension	Non-applicable	Moist soil	Yes
Xylene	Кос	202	Henry	524,86 Pa·m ³ /mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes
Ethylbenzene	Кос	520	Henry	798,44 Pa·m ³ /mol
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes
EC: 202-849-4	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes
2-(2-butoxyethoxy)ethanol	Кос	48	Henry	7,2E-9 Pa·m³/mol
CAS: 112-34-5	Conclusion	Very High	Dry soil	No
EC: 203-961-6	Surface tension	3,395E-2 N/m (25 °C)	Moist soil	No
Toluene	Кос	178	Henry	672,8 Pa·m³/mol
CAS: 108-88-3	Conclusion	Moderate	Dry soil	Yes
EC: 203-625-9	Surface tension	2,793E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

	Code	Description	Waste class (Regulation (EU) No 1357/2014)
I	08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:



SECTION 13: DISPOSAL CONSIDERATIONS (continued)

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:

inan egara te / E					
	14.1	UN number:	UN1263		
A AV	14.2	UN proper shipping name:	PAINT		
〈''〉 〈'垫〉	14.3	Transport hazard class(es):	3		
\checkmark \checkmark		Labels:	3		
	14.4	Packing group:	III		
	14.5	Environmental hazards:	Yes		
	14.6	Special precautions for user			
		Special regulations:	163, 367, 640E, 650		
		Tunnel restriction code:	D/E		
		Physico-Chemical properties:	see section 9		
		Limited quantities:	5 L		
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable		
Transport of da	ngerou	s goods by sea:			
With regard to IM	DG 38-	16:			
	14.1	UN number:	UN1263		
	14.2	UN proper shipping name:	PAINT		
	14.3	Transport hazard class(es):	3		
		Labels:	3		
\checkmark	14.4	Packing group:	III		
	14.5	Environmental hazards:	Yes		
	14.6	Special precautions for user			
		Special regulations:	223, 955, 163, 367		
		EmS Codes:	F-E, S-E		
		Physico-Chemical properties:	see section 9		
		Limited quantities:	5 L		
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable		
Transport of da	ngerou	s goods by air:			
With regard to IATA/ICAO 2017:					
	14.1	UN number:	UN1263		
〈"〉 〈鉴〉	14.2	UN proper shipping name:	PAINT		
\checkmark	14.3	Transport hazard class(es):	3		
		Labels:	3		
	14.4	Packing group:	III		
	14.5	Environmental hazards:	Yes		
	14.6	Special precautions for user			
		Physico-Chemical properties:	see section 9		
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable		

SECTION 15: REGULATORY INFORMATION



SECTION 15: REGULATORY INFORMATION (continued)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 2-phenoxyethanol.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

----ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains Octamethylcyclotetrasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

Removed substances

Dipropylene Glycol Methyl Ether (34590-94-8)

Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness

- H411: Toxic to aquatic life with long lasting effects
- H373: May cause damage to organs through prolonged or repeated exposure

H226: Flammable liquid and vapour

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:



SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 4: H302 - Harmful if swallowed Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled Acute Tox, 4: H312 - Harmful in contact with skin Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled Acute Tox. 4: H332 - Harmful if inhaled Aquatic Acute 1: H400 - Very toxic to aquatic life Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways Carc. 2: H351 - Suspected of causing cancer Eye Dam. 1: H318 - Causes serious eye damage Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 2: H225 - Highly flammable liquid and vapour Flam. Lig. 3: H226 - Flammable liquid and vapour Repr. 2: H361d - Suspected of damaging the unborn child. Repr. 2: H361f - Suspected of damaging fertility. Skin Irrit. 2: H315 - Causes skin irritation Skin Sens. 1: H317 - May cause an allergic skin reaction STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral) STOT SE 3: H335 - May cause respiratory irritation STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure:

STOT SE 3: Calculation method Aquatic Chronic 2: Calculation method STOT RE 2: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LOg-POW: Octanol–water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.