



DESCRIPTION

MINOS XD 500 is a high performance multi-purpose lubricant – corrosion protector – deep penetrating – water displacement product. Exhibits superior protection and lubrication, prevents rust and corrosion by displacing moisture and leaving behind a thin, clear, protective film. It also releases rusted parts, removes light soils and contaminants.

ADVANTAGES

- Excellent penetrating properties
- Weather resistant
- Moisture repellent
- Effective rust remover
- Corrosion protection
- Easy to use
- Environmentally friendly

APPLICATIONS

MINOS XD 500 has thousands of uses around the house, at work, hobbies etc.

- Loosens and penetrates rusted or stuck bolts and plumbing joints
- Protects metal from rust and corrosion
- Displaces moisture and lubricates just about anything
- Penetrates stuck parts
- Eliminates squeaks
- Cleans bikes & tools, removes grease, lubricates locks, hinges, & all moving parts
- Removes paint, gum, rubber cement, stickers and other adhesives
- Removes dirt, dust, petroleum and water

METHOD OF APPLICATION

1. Before use, shake the can for 2 minutes
2. Apply one layer of MINOS XD 500 from a distance to the surface to be treated approximately 25 to 30cm
3. Allow product to soak for 5 - 15 minutes and if needed apply a second layer
4. Optimum result is obtained after evaporation of the solvents.
5. After use, turn can upside down and press the nozzle for 5" to clean the valve.

CLEANING

With soap and water immediately after use

CONSUMPTION

Depends on application

TECHNICAL DATA

Type: Anticorrosive - lubricant

Form: Liquid

Colour: Transparent

Relative density: 0,85 gr/ml

Application temperature: 10°C - 30°C

VOC (Volatile Organic Compounds) CONTENT: (Directive 2004/42/CE)

EU maximum VOC content limit values for this product (category B e 'Special finishes'): 840 gr/lit (2010). This product contains maximum 820 gr/lit VOCs (ready for use product).

STORAGE

In a cool and dry place at temperatures between +5°C - +25°C away from sources of ignition. Avoid direct sunlight.

SHELF LIFE

At least 5 years in unopened original package, under above mentioned storage conditions.

PACKAGING

Spray 400ml

PACKAGING	CODE	BARCODE
400ml	9205	5204094092056

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION



Aerosol 1: H229 - Pressurized container: May burst if heated
Aerosol 1: H222 - Extremely flammable aerosol
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects
Eye Irrit. 2: H319 - Causes serious eye irritation
Repr. 1B: H360D - May damage the unborn child.
Skin Irrit. 2: H315 - Causes skin irritation
STOT SE 3: H335 - May cause respiratory irritation
P101: If medical advice is needed, have product container or label at hand
P102: Keep out of reach of children
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211: Do not spray on an open flame or other ignition source
P251: Do not pierce or burn, even after use
P280: Wear protective gloves/protective clothing/eye protection/face protection
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F
P501: Dispose of contents and / or their container according to the separated collection system used in your municipality
EUH066: Repeated exposure may cause skin dryness or cracking. Substances that contribute to the classification: N-methyl-2-pyrrolidone; Organic modified polydimethylsiloxane ; 1,2,4-trimethylbenzene; Mesitylene
Restricted to professional users

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.

