

DESCRIPTION

Chalk Effect spray paint that creates an even, ultra-matte finish to transform your furniture and all decorative objects. Ideal for wooden surfaces but also metal, stone, ceramics and marble.

INSTRUCTIONS FOR USE

General Instructions for spray paints:

Shake the container at least 3 minutes after you hear the ball mixer. Before the first use spray it in the air for 3-4 seconds to remove any condensed color. After Use hold the aerosol upside down and press the actuator for 2-3 seconds to clean the valve. If the nozzle is blocked, replace it with a new one. Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 10-32°C and humidity is below 65% to ensure proper drying. Do not use on objects that may exceed 90°C surface temperature. Storage 10-30°C.

Specific Instructions for Chalk Effect:

1. Choose a well-ventilated area and place the object you want to paint over a nylon protection sheet.
2. Ensure that the object you want to paint is clean, dry and free of loose spots or grease.
3. Old wooden furniture may have been polished with wax. If so, use a wire sponge with white spirit to clean it before painting. For painted wood ideally sand it before painting it with a P180 sandpaper.
4. Mask areas that you do not want to be painted with a paper tape.
5. Apply two coats of the Chalk Effect with relatively quick movements at a distance of 10-15 cm. Paint first vertically and then horizontally (this is one coat). Wait 10 minutes before painting the next coat.
6. For small objects or areas that need detailed painting, use the white nozzle (from a distance of 10cm) that you will find on the package. For larger surfaces and high speed use the black nozzle (from a distance of 15cm)
7. The result of the above steps will be a luxurious and uniform matte surface. If you want to add the effect of natural wear, 1 hour after painting use a fine sandpaper P180- 220 and gently rub the colored areas you want to remove, exposing the bare wood -this usually works best on the edges and corners.
8. You can also use 2 different colors, a light base color (Chalk Effect Pure White) and a second color on top. When you rub the exterior paint instead of wood the base color will be revealed.
9. The Chalk Effect series gives a permanent effect that lasts over time. For even more durability, use the Chalk Varnish matte varnish from the Chalk Effect series.

PHYSICAL PROPERTIES

Viscosity: 18-25 sec (Flow Cup DIN4, 20oC)
 Density: 0.80 - 0.85 kg/L (Density Cup 100cm3/ 20oC, ASTM D-1475)
 Solids: 23-26%
 Flash Point: -104 oC (based on propellant)
 Available Colours: 14 shades according CL Chalk color index
 Drying time: Touch (20°C, Humidity<65%): 5-10min. | Through dry (20°C, Humidity <65%) : 1h. | Maximum hardness: 24 hours
 Coverage: 4m² / 400ml
 Gloss: 2-4(60°)
 Can Pressure: 4bar (20 °C) , 8 bar (50 °C)
 Contents: 400ml
 Shelf life: minimum 5 years.
 VOC content: 620 g/L
 After Use: Spray holding the can inverted for 3". | Clean the caps with solvent.
 Storage: 5-35°C. Do not put in vehicles.

FEATURES

- Extreme coverage.
- Matte effect.
- With 2 actuators for small or big surfaces.
- Fast drying.
- Doesn't drip
- Easily sandable
- Easy to apply and recoat.
- Does not contain lead.
- Very good resistance to the sun and rain.
- Rust preventative.
- Excellent elasticity.

APPEARANCE



CAP SYSTEM



CAUTION

