



Adhesives & Sealants

W FIX MONTAGE

Technical Data Sheet

Reviewed: 06.08.2019



DESCRIPTION

W FIX MONTAGE is a ready to use waterbased assembly adhesive. It replaces the use of nails and screws in many applications. It is an excellent value for money solution for easy applications.

ADVANTAGES

- Extra strong bonding
- High yield
- Fast application
- Wide range of applications
- Bonds on uneven substrates
- Solvent free – friendly to the environment
- Interior and exterior use

APPLICATIONS

- Assembling and fixing in building and renovation – home improvement projects
- Suitable for bonding and fixing door signs, profiles, architraves, skirting boards, sills, cable ducts, panels, decorative profiles, ceramic tiles, bricks, metals etc.
- Bonds stone, brick, wood, expanded and extruded polystyrene panels, metal, plastics (except PS, PE, PP) and much more

INSTRUCTIONS FOR USE

1. Surfaces must be dry and clean free from dust and grease
2. Use caulking gun
3. Apply dots or stripes of approx. 20 cm apart
4. Place the component into place by shoving and pushing firmly
5. If necessary (for heavy materials) support until the adhesive is fully cured (24 hours).

A suitability test is recommended

CLEANING

Clean all equipment with water immediately after use

CONSUMPTION

300-1000 gr/m² or 25-40 gr/m

TECHNICAL CHARACTERISTICS

Form: Paste
Colour: Off white
Smell: Characteristic
Viscosity: 65000 mpas 25 °C
Specific gravity: 1.5 ± 0.15 gr/cm³ 25°C
PH: 8 – 9
Flammable: No
Open time: 5-10 min (23°C/ 55% R.F.)
Final adhesion: 24h
Temperature Resistance: -20°C - +70°C.
Application temperature: +5°C - +30°C.

STORAGE

In a cool and dry place at temperatures between +5°C - +25°C

SHELF LIFE

24 months in unopened packaging in the above mentioned storage conditions

PACKAGING

Cartridges 280ml

| PACKAGING | CODE | BARCODE |
|-----------|-------|---------------|
| 280ml | 04251 | 5204094042167 |

HEALTH AND SAFETY INFORMATION

P101 If medical advice is needed, have product container or label at hand
 P102 Keep out of reach of children
 P103 Read label before use
 P501: Dispose of contents and / or their container according to the separated collection system used in your municipality

Evochem®

EVOCHEM S.A.

Tzaverdella place 13341, Fyli, Attica, Greece

Tel.: 210 5590460, 210 5590155 Fax: 210 5590244

E-mail: info@evochem.gr Website: www.evochem.gr





Adhesives & Sealants

W FIX MONTAGE

Technical Data Sheet

Reviewed: 06.08.2019

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



Evochem®

EVOCHEM S.A.
Tzavardella place 13341, Fyli, Attica, Greece
Tel.: 210 5590460, 210 5590155 Fax: 210 5590244
E-mail: info@evochem.gr Website: www.evochem.gr

