

Color has a Name!

### WRITE OFF A COMPONENT

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### Product identifier: WRITE OFF A COMPONENT 1.1

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Special coatings. For professional user/industrial user only.

Board marker varnish

Uses advised against: All uses not specified in this section or in section 7.3

#### 1.3 Details of the supplier of the safety data sheet:

Berling S.A. Thesi Agia Paraskevi 32011 Inofvta Viotias - Greece Phone.: +302262031663 - Fax: +302262031293 info@berling.gr www.berling.gr

1.4 Emergency telephone number: +30 210 7793 777 (Greek Poison Info Center)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture:

### CLP Regulation (EC) No 1272/2008:

The product is not classified as hazardous according to CLP Regulation (EC) No 1272/2008.

#### 2.2 Label elements:

### CLP Regulation (EC) No 1272/2008:

Hazard statements:

Non-applicable

#### **Precautionary statements:**

Non-applicable

### Supplementary information:

EUH208: Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction

EUH210: Safety data sheet available on request

#### 2.3 Other hazards:

Product contains PBT/vPvB substances: Decamethylcyclopentasiloxane, Octamethylcyclotetrasiloxane, Dodecamethylcyclohexasiloxane

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\*

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

Chemical description: Aqueous mixture composed of polyurethane resins and various additives

### **Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification	Chemical name/Classification		Concentration	
CAS:		3-butoxypropan-2-ol	-butoxypropan-2-ol <sup>(1)</sup> ATP CLP00		
	225-878-4 603-052-00-8 01-2119475527-28- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	(1)	2,4 - <4,9 %

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

\*\* Changes with regards to the previous version



### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

### By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

#### By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

#### By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use full jet water as an extinguishing agent.

### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

#### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

#### 6.3 Methods and material for containment and cleaning up:

#### It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

### 6.4 Reference to other sections:

See sections 8 and 13.

### SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

### 7.2 Conditions for safe storage, including any incompatibilities:

	<b>j</b> -,
A Technical measures for s	storage
Minimum Temp.:	5 °C
Maximum Temp.:	35 °C
Maximum time:	0 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Er	vironmental limits	
Dipropylene Glycol Methyl Ether	IOELV (8h)	50 ppm	308 mg/m <sup>3</sup>
CAS: 34590-94-8 EC: 252-104-2	IOELV (STEL)		
2-(2-butoxyethoxy)ethanol	IOELV (8h)	10 ppm	67.5 mg/m <sup>3</sup>
CAS: 112-34-5 EC: 203-961-6	IOELV (STEL)	15 ppm	101.2 mg/m <sup>3</sup>

### DNEL (Workers):

		Short e	xposure	Long ex	kposure
Identification		Systemic	Local	Systemic	Local
3-butoxypropan-2-ol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 5131-66-8	Dermal	Non-applicable	Non-applicable	44 mg/kg	Non-applicable
EC: 225-878-4	Inhalation	Non-applicable	Non-applicable	270,5 mg/m <sup>3</sup>	Non-applicable

#### DNEL (General population):

		Short e	xposure	Long ex	kposure
Identification		Systemic	Local	Systemic	Local
3-butoxypropan-2-ol O	Dral	Non-applicable	Non-applicable	8,75 mg/kg	Non-applicable
CAS: 5131-66-8	Permal	Non-applicable	Non-applicable	16 mg/kg	Non-applicable
EC: 225-878-4 Ir	nhalation	Non-applicable	Non-applicable	33,8 mg/m <sup>3</sup>	Non-applicable



### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
3-butoxypropan-2-ol	STP	10 mg/L	Fresh water	0,525 mg/L
CAS: 5131-66-8	Soil	0,16 mg/kg	Marine water	0,0525 mg/L
EC: 225-878-4	Intermittent	5,25 mg/L	Sediment (Fresh water)	2,36 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,236 mg/kg

### 8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

#### C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2003+A1:2009 and EN ISO 374-1:2016

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

#### D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

### E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes		EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
+	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	<b>0</b> +	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

#### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

Not available

V.O.C. (Supply):



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

V.O.C. density at 25 °C:	Not available
Average carbon number:	Not available
Average molecular weight:	Not available
With regard to Directive 2004/42/EC, thi	s product which is ready to use has the following characteristics:
V.O.C. density at 25 °C:	70 kg/m³ (70 g/L)
EU limit for the product (Cat. A.L): 2	200 g/L (2010)
Components:	NEPO - 13,3 % v/v ; WRITE OFF B COMPONENT - 20 % v/v

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

For complete information see the product datash	neet.
Appearance:	
Physical state at 20 °C:	Liquid
Appearance:	Not available
Colour:	Colourless
Odour:	Not available
Odour threshold:	Non-applicable *
Volatility:	
Boiling point at atmospheric pressure:	112 °C
Vapour pressure at 25 °C:	3073 Pa
Vapour pressure at 50 °C:	11954,82 Pa (11,95 kPa)
Evaporation rate at 25 °C:	Non-applicable *
Product description:	
Density at 25 °C:	970 - 1030 kg/m³
Relative density at 25 °C:	Non-applicable *
Dynamic viscosity at 25 °C:	Non-applicable *
Kinematic viscosity at 25 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 25 °C:	Non-applicable *
Partition coefficient n-octanol/water 25 °C:	Non-applicable *
Solubility in water at 25 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Flammability:	
Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	204 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *
Explosive:	



SECT	SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)							
Evelocitor Lower explosive limit: Non-applicable *								
	Upper explosive limit:	Non-applicable *						
9.2	Other information:							
	Surface tension at 25 °C:	Non-applicable *						
	Refraction index:	Non-applicable *						
	*Not relevant due to the nature of the product, not providing information property of its hazards.							

### SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

### **10.2** Chemical stability:

Chemically stable under the conditions of storage, handling and use.

#### **10.3** Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
				·

### **10.5** Incompatible materials:

Acids	Acids Water		Combustible materials	Others	
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases	

### **10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.

- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):



### SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3. IARC: 2,2',2''-nitrilotriethanol (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

### Other information:

Non-applicable

### Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
3-butoxypropan-2-ol	LD50 oral	3771 mg/kg	Rat
CAS: 5131-66-8	LD50 dermal	>2000 mg/kg	
EC: 225-878-4	LC50 inhalation	>20 mg/L (4 h)	

### SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification		Acute toxicity	Species	Genus
3-butoxypropan-2-ol	LC50	560 mg/L (96 h)	Poecilia reticulada	Fish
CAS: 5131-66-8	EC50	1436 mg/L (48 h)	Daphnia magna	Crustacean
EC: 225-878-4	EC50	Non-applicable		

### **12.2** Persistence and degradability:

Identification	Degradability		Biodegradability		
-butoxypropan-2-ol BOD5 Non-applica		Non-applicable	Concentration	100 mg/L	
CAS: 5131-66-8	COD	Non-applicable	Period	28 days	
EC: 225-878-4 BOD5/COD		Non-applicable	% Biodegradable	89 %	

#### 12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential		
3-butoxypropan-2-ol	BCF	1	
CAS: 5131-66-8	Pow Log		
EC: 225-878-4	Potential	Low	
.4 Mobility in soil:	•		

Not available

1

#### 12.5 Results of PBT and vPvB assessment:



### SECTION 12: ECOLOGICAL INFORMATION (continued)

Product contains PBT/vPvB substances: Decamethylcyclopentasiloxane, Octamethylcyclotetrasiloxane, Dodecamethylcyclohexasiloxane

### **12.6** Other adverse effects:

Not described

### SECTION 13: DISPOSAL CONSIDERATIONS

### **13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 12	waste paint and varnish other than those mentioned in 08 01 11	Non dangerous

### Type of waste (Regulation (EU) No 1357/2014):

Non-applicable

### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

### **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

### SECTION 14: TRANSPORT INFORMATION

### Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:

14.1	UN number:	Non-applicable
14.2	UN proper shipping name:	Non-applicable
14.3	Transport hazard class(es):	Non-applicable
	Labels:	Non-applicable
14.4	Packing group:	Non-applicable
14.5	Environmental hazards:	No
14.6	Special precautions for user	
	Special regulations:	Non-applicable
	Tunnel restriction code:	Non-applicable
	Physico-Chemical properties:	see section 9
	Limited quantities:	Non-applicable
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable
Transpor	t of dangerous goods by sea:	
With rega	rd to IMDG 39-18:	



SE

### WRITE OFF A COMPONENT

CTION 14: T	RANSPORT INFORMATION (co	ntinued)
14.1	UN number:	Non-applicable
14.2	•••• F•• F••• •••• FF••• <b>5</b> ••••••	Non-applicable
14.3	Transport hazard class(es):	Non-applicable
	Labels:	Non-applicable
14.4	·	Non-applicable
14.5	Environmental hazards:	No
14.6	Special precautions for user	
	Special regulations: EmS Codes:	Non-applicable
	Physico-Chemical properties:	see section 9
	Limited quantities:	Non-applicable
	Segregation group:	Non-applicable
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable
Transpor	t of dangerous goods by air:	
With rega	rd to IATA/ICAO 2020:	
14.1	UN number:	Non-applicable
14.2	UN proper shipping name:	Non-applicable
14.3	Transport hazard class(es):	Non-applicable
	Labels:	Non-applicable
14.4	Packing group:	Non-applicable
14.5	Environmental hazards:	No
14.6	Special precautions for user	
	Physico-Chemical properties:	see section 9
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable

### SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 1,2benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,3bis(hydroxymethyl)-5,5-dimethylimidazolidine-2,4-dione, (ethylenedioxy)dimethanol.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

#### Seveso III:

Non-applicable

# Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Contains Octamethylcyclotetrasiloxane, Decamethylcyclopentasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

### Other legislation:

The product could be affected by sectorial legislation



Product safety information sheet according to REACH (article 32)

### WRITE OFF A COMPONENT

### Color has a Name!

### SECTION 15: REGULATORY INFORMATION (continued)

### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

### SECTION 16: OTHER INFORMATION

### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

Removed substances

2-amino-2-methyl-1-propanol (124-68-5)

### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### CLP Regulation (EC) No 1272/2008:

Eye Irrit. 2: H319 - Causes serious eye irritation

Skin Irrit. 2: H315 - Causes skin irritation

## **Classification procedure:**

Non-applicable

### Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

#### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

Product safety information sheet prepared in accordance with Article 32 of Regulation (EC) 1907/2006 (REACH); this document does not constitute a Safety Data Sheet under Article 31 of 1907/2006, mandatory Regulation No. Safety Data Sheet not for this (EC) as а is produc The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.



### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### Product identifier: WRITE OFF B COMPONENT 1.1

#### 12 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Hardener for coatings. For professional user/industrial user only.

Not suitable for do it yourself uses

Uses advised against: All uses not specified in this section or in section 7.3

#### 1.3 Details of the supplier of the safety data sheet:

Berling S.A. Thesi Agia Paraskevi 32011 Inofyta Viotias - Greece Phone.: +302262031663 - Fax: +302262031293 info@berling.gr www.berling.gr

1.4 Emergency telephone number: +30 210 7793 777 (Greek Poison Info Center)

### SECTION 2: HAZARDS IDENTIFICATION \*\*

#### Classification of the substance or mixture: 2.1

### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute inhalation toxicity, Category 4, H332 Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412 Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 3: Flammable liquids, Category 3, H226 Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1B: Sensitisation, skin, Category 1B, H317 STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

#### 2.2 Label elements:

### CLP Regulation (EC) No 1272/2008:

### Warning



#### Hazard statements:

Acute Tox. 4: H332 - Harmful if inhaled Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 3: H226 - Flammable liquid and vapour Skin Irrit. 2: H315 - Causes skin irritation Skin Sens. 1B: H317 - May cause an allergic skin reaction STOT SE 3: H335 - May cause respiratory irritation

#### **Precautionary statements:**

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P280: Wear protective gloves/protective clothing/eye protection/face protection P284: Wear respiratory protection P302+P352: IF ON SKIN: Wash with plenty of water P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P370+P378: In case of fire: Use ABC powder extinguisher to extinguish P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment Supplementary information: EUH204: Contains isocyanates. May produce an allergic reaction

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

Revised: 03/07/2020



### SECTION 2: HAZARDS IDENTIFICATION \*\* (continued)

Substances that contribute to the classification

Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI) (CAS: 666723-27-9)

### 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

\*\* Changes with regards to the previous version

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\*

### 3.1 Substance:

Non-applicable

### 3.2 Mixture:

### Chemical description: Mixture of isocyanates and other substances

### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification Chemical name/Classification 0			Concentration	
CAS:	666723-27-9 Non-applicable Non-applicable Non-applicable	<b>Blocked Polyisocyana</b>	te Based on Hexamethylene Diisocyanate (HDI) <sup>(1)</sup> Self-class	ified	
EC: Index: REACH:		Regulation 1272/2008	Acute Tox. 4: H332; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1B: H317; STOT SE 3: H335 - Warning	()	50 - <75 %
CAS: EC: Index: REACH:	108-65-6 203-603-9 607-195-00-7 01-2119475791-29- XXXX	2-methoxy-1-methyle	thyl acetate <sup>(2)</sup> ATP ATPC	1	
		Regulation 1272/2008	Flam. Liq. 3: H226 - Warning	٨	24 - <50 %
			hich meet criteria laid down in Regulation (EU) No. 2015/830		

<sup>(2)</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

\*\* Changes with regards to the previous version

### SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.



### SECTION 4: FIRST AID MEASURES (continued)

### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

### 6.4 Reference to other sections:

See sections 8 and 13.

### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions



### SECTION 7: HANDLING AND STORAGE (continued)

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:5 °CMaximum Temp.:35 °CMaximum time:0 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Occupational exposure limits			
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m <sup>3</sup>	
CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m <sup>3</sup>	

### DNEL (Workers):

		Short e	xposure	Long ex	posure
Identification		Systemic	Local	Systemic	Local
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	153,5 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	275 mg/m <sup>3</sup>	Non-applicable

### DNEL (General population):

		Short e	xposure	Long ex	kposure
Identification		Systemic	Local	Systemic	Local
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	1,67 mg/kg	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	54,8 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m <sup>3</sup>	Non-applicable

#### PNEC:

Identification				
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,0635 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg

#### 8.2 Exposure controls:

A.- General security and hygiene measures in the work place



### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2003+A1:2009 and EN ISO 374-1:2016

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

### D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2001 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN ISO 13287:2012 EN ISO 20345:2011	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

#### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

- V.O.C. (Supply):Not availableV.O.C. density at 25 °C:Not available



### Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## WRITE OFF B COMPONENT

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Average carbon number:Not availableAverage molecular weight:Not availableWith regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:V.O.C. density at 25 °C:70 kg/m³ (70 g/L)EU limit for the product (Cat. A.L):200 g/L (2010)Components:Non-applicable

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1	Information on basic physical and chemical pr	Information on basic physical and chemical properties:				
	For complete information see the product datasheet.					
	Appearance:					
	Physical state at 20 °C:	Liquid				
	Appearance:	Not available				
	Colour:	Not available				
	Odour:	Not available				
	Odour threshold:	Non-applicable *				
	Volatility:					
	Boiling point at atmospheric pressure:	146 °C				
	Vapour pressure at 25 °C:	515 Pa				
	Vapour pressure at 50 °C:	2289,67 Pa (2,29 kPa)				
	Evaporation rate at 25 °C:	Non-applicable *				
	Product description:					
	Density at 25 °C:	1080 - 1120 kg/m³				
	Relative density at 25 °C:	Non-applicable *				
	Dynamic viscosity at 25 °C:	3,02 cP				
	Kinematic viscosity at 25 °C:	2,85 cSt				
	Kinematic viscosity at 40 °C:	Non-applicable *				
	Concentration:	Non-applicable *				
	pH:	Non-applicable *				
	Vapour density at 25 °C:	Non-applicable *				
	Partition coefficient n-octanol/water 25 °C:	Non-applicable *				
	Solubility in water at 25 °C:	Non-applicable *				
	Solubility properties:	Non-applicable *				
	Decomposition temperature:	Non-applicable *				
	Melting point/freezing point:	Non-applicable *				
	Explosive properties:	Non-applicable *				
	Oxidising properties:	Non-applicable *				
	Flammability:					
	Flash Point:	45 °C				
	Flammability (solid, gas):	Non-applicable *				
	Autoignition temperature:	315 ℃				
	Lower flammability limit:	Not available				
	Upper flammability limit:	Not available				
	Explosive:					
	*Not relevant due to the nature of the product, not providing inf	ormation property of its hazards.				



SECT	TION 9: PHYSICAL AND CHEMICAL PF	OPERTIES (continued)			
	Lower explosive limit:	Non-applicable *			
	Upper explosive limit:	Non-applicable *			
9.2	Other information:				
	Surface tension at 25 °C:	Non-applicable *			
	Refraction index:	Non-applicable *			
	*Not relevant due to the nature of the product, not providing information property of its hazards.				
SECT	TION 10: STABILITY AND REACTIVIT	ſ			

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### **10.4** Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

### **10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
  - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
  - Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
  - Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

### - CONTINUED ON NEXT PAGE -

Revised: 03/07/2020



### SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3. IARC: Non-applicable
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

#### Other information:

Non-applicable

### Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI)	LD50 oral	>2000 mg/kg	
CAS: 666723-27-9	LD50 dermal	>2000 mg/kg	
EC: Non-applicable	LC50 inhalation	11 mg/L (4 h) (ATEi)	
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	5100 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat

### SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

### 12.1 Toxicity:

Identification		Acute toxicity	Species	Genus
Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI)	LC50	10 - 100 mg/L (96 h)		Fish
CAS: 666723-27-9	EC50	10 - 100 mg/L		Crustacean
EC: Non-applicable	EC50	10 - 100 mg/L		Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Non-applicable		

### 12.2 Persistence and degradability:

	Identification	Degradability		Biodegradability	
	2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
	CAS: 108-65-6	COD	Non-applicable	Period	8 days
	EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
12.3	Bioaccumulative potential:				

Revised: 03/07/2020



	Identification	Bio	Bioaccumulation potential	
	2-methoxy-1-methylethyl acetate	BCF	1	
	CAS: 108-65-6	Pow Log	0.43	
	EC: 203-603-9	Potential	Low	
2.4	Mobility in soil:			
	Not available			
2.5	Results of PBT and vPvB assessment:			
	Product fails to meet PBT/vPvB criteria			
2.6	Other adverse effects:			

### SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous	

### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

### **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

### SECTION 14: TRANSPORT INFORMATION

#### Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:

14.2	UN number: UN proper shipping name: Transport hazard class(es): Labels:	UN1263 PAINT RELATED MATERIAL 3 3
14.4	Packing group:	III
14.5	Environmental hazards:	No
14.6	Special precautions for user	
	Special regulations:	163, 367, 650
	Tunnel restriction code:	D/E
	Physico-Chemical properties:	see section 9
	Limited quantities:	5 L
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable
Transport of danger	ous goods by sea:	
With regard to IMDG 39	)-18:	



SECTION 14: TRANSPORT INFORMATION (continued)				
	14.2	UN number: UN proper shipping name: Transport hazard class(es):	UN1263 PAINT RELATED MATERIAL 3	
	14.4	Labels: Packing group:	3 III	
		Environmental hazards:	No	
0	14.6	Special precautions for user		
		Special regulations:	163, 223, 955, 367	
		EmS Codes:	F-E, S-E	
		Physico-Chemical properties:	see section 9	
		Limited quantities:	5 L	
		Segregation group:	Non-applicable	
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable	
Transport of dan	Igerou	is goods by air:		
With regard to IAT	A/ICA	O 2020:		
	14.1	UN number:	UN1263	
where a	14.2	UN proper shipping name:	PAINT RELATED MATERIAL	
	14.3	Transport hazard class(es):	3	
		Labels:	3	
3	14.4	Packing group:	III	
•	14.5	Environmental hazards:	No	
	14.6	Special precautions for user		
		Physico-Chemical properties:	see section 9	
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable	

### SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

## Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements			
P5c		5000	50000			
Limitations ):	imitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ):					



Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## WRITE OFF B COMPONENT

### SECTION 15: REGULATORY INFORMATION (continued)

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration,

- metallic glitter intended mainly for decoration
  artificial snow and frost.
- "whoopee" cushions,
- whoopee cushions,
  silly string aerosols,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Shall not be used in:

---ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

### Other legislation:

The product could be affected by sectorial legislation

### Other information:

The following information for isocyanate coating materials is provided by the European Committee of Manufacturers of Varnishes and Paints - CEPE - The coating materials prepared with isocyanates can cause irritation to the mucous membranes, especially on the mucous membranes. respiratory organisms, and hypersensitivity.

When inhalation of vapors or spraying nebula, there is a risk of sensitization. When handling isocyanate-based coatings, all safety measures for coatings containing solvents should be carefully considered. Inhalation of vapors and vapors is prohibited. Allergic, asthmatic, and generally people susceptible to respiratory diseases should not come into contact with coating materials containing isocyanates.

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

### SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

Removed substances

- Hexamethylene-di-isocyanate (822-06-0)
- Cyclohexyldimethylamine (98-94-2)
- (2,4,6-trioxotriazine-1,3,5(2H,4H,6H)-triyl)tris(hexamethylene) isocyanate (3779-63-3)
- Substances that contribute to the classification (SECTION 2):
- New declared substances

Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI) (666723-27-9)

### Texts of the legislative phrases mentioned in section 2:

- H315: Causes skin irritation
- H335: May cause respiratory irritation
- H412: Harmful to aquatic life with long lasting effects
- H317: May cause an allergic skin reaction
- H332: Harmful if inhaled
- H226: Flammable liquid and vapour
- H319: Causes serious eye irritation



## SECTION 16: OTHER INFORMATION (continued)

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H332 - Harmful if inhaled Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 3: H226 - Flammable liquid and vapour Skin Irrit. 2: H315 - Causes skin irritation Skin Sens. 1B: H317 - May cause an allergic skin reaction STOT SE 3: H335 - May cause respiratory irritation

### Classification procedure:

Skin Irrit. 2: Calculation method STOT SE 3: Calculation method Aquatic Chronic 3: Calculation method Skin Sens. 1B: Calculation method Acute Tox. 4: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3) Eye Irrit. 2: Calculation method

#### Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

#### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.