

VITEX METALLICO

Emulsion Paint With Metallic Finish

Water-based paint, based on specific acrylic resins and metallic pigments, formulated specially in order to provide an impressive metallic finish on every surface. It can be applied on to walls, pillars, ceilings, plasterboards as well as wood, plastic or metal, after proper preparation. Virtually odourless during its application, since it does not contain ammonia or any other dangerous substances, such as aromatic hydrocarbons, free formaldehyde, heavy metals or alkylphenolethoxylates.



Advantages:

- Impressive metallic finish for exceptional and easy styles
- For every surface, even for wood, plastic and metal
- Ready in 3 and painted in 30 shades

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS

Viscosity

80 ± 10 KU (ASTM D 562, 25°C)




Density

1,10 ± 0,02 Kg / L (ISO 2811) for white

Gloss

> 25 units @ 60° (ISO 2813)

COVERAGE



One coat

10-12 m²/L



Two coats

5-6 m²/L

PACKAGING

Silver, Gold, Bronze	700 mL	2.1 L
Base Pandora	700 mL	2.1 L

FINISH

Mat	Satin	Metallic
		✓
Metallic Finish		

DILUTION



Water

- 0-5 % for painting with a roller or brush
- 5-10% for painting with spray gun

DRYING TIME



Touch dry


1-2 h

Recoat

6-8 h


COLOURS

500 Pandora (silver), 520 Helios (gold) and 530 Selene (copper).



The 500 Pandora tint is also used as the base for creating 30 recommended chromatology shades through the **Vitex Coloring System**

COLOR CARDS - FANDECKS



INTERIOR USE

APPLICATION

APPLICATION FIELD

For the decoration of walls, columns, ceilings, plasterboard, but also surfaces of wood, plastic or metal, after proper preparation.

ΠΡΟΕΡΓΑΣΙΑ



Surfaces should be clean, dry and smooth, free from dust, grease and loose or flaking paint.

To fill any cracks or holes use Acrylic Putty or Visto.



Surfaces previously covered with water paints or distempers (lime wash or ceiling white) should be primed with Acrylan Unco Eco or Durovit.

New surfaces made of plaster, concrete, cement, plasterboard, etc. should be first primed with 100% Acrylic Primer or Acrylan Unco Eco. For a better highlight of the metallic finish, it is recommended to apply a layer of a Vitex emulsion paint before applying Vitex Metallico.



Wood, PVC, aluminium and galvanized steel surfaces should be first coated with either Velatura Eco or Primer for Glossy Surfaces.

Metal surfaces should be coated with an anti-rust primer (Anti-Rust Primer or Metal Primer).



STEPS

- 1 Stir well before use and periodically during application. Dilute with water before use.
- 2 Apply the first coat by brush, roller or airless spray gun.
- 3 Recoat after 6-8 hours.

TIPS

- Application at 5-35°C and <80% RH.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Allow at least 3 weeks before cleaning and washing newly painted surfaces with Vitex Metallico. Wash gently with water using a soft sponge. In case of tough stains, use a mild colourless detergent or soapy water.
- Recover unused paint for re-use. After paint application, seal the container and store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.
- Minimize paint wastage by estimating how much paint you will need.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Interior glossy walls and ceilings (Gloss >25@60°)" VOC content limit **100 g/L**. Maximum VOC content **29 g/L** (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

ISO 9001
14001
CERTIFIED 45001

