



## Cleaners

# CL 44 ALUMINIUM CLEANER

### Technical Data Sheet

Reviewed: 30.07.2018



#### DESCRIPTION

**CL 44 ALUMINIUM CLEANER** is a special cleaner for anodized and coated aluminium surfaces without altering or affecting their original colour. Its unique formula enables easy removal of difficult stains, deposits from environmental pollution, tough soil, smudges and salt stains as well as fresh residues from waterbased paints.

#### ADVANTAGES

- Immediate action in 5 minutes
- Suitable for electrostatic coated aluminium surfaces

#### APPLICATIONS

- It is suitable for any kind of aluminium surface such as window and door frames, doors, stairs, accessories and all kinds of aluminium constructions.

#### INSTRUCTIONS FOR USE

1. Shake well before using.
2. Remove safety cover from valve.
3. Apply evenly from a distance of 5-10cm.
4. Rub lightly with a soft cloth or sponge.
5. Wash the surface with clean water and buff with a dry cotton cloth.
6. Follow the same procedure again for difficult spots/areas.

#### CONSUMPTION

7-8m<sup>2</sup>/Lt

#### TECHNICAL CHARACTERISTICS

**Form:** Liquid  
**Color:** Transparent  
**Odour:** Characteristic of acid  
**Density:** 1,00 ± 0.02 gr/cm<sup>3</sup>25 °C  
**Flammability:** Non Flammable  
**Solubility in water:** Unlimited  
**Application temperature:** +5°C έως +35°C

#### REMARKS

- Wear protective gloves before application.
- Avoid spraying on open sockets and electricity wires.
- Before use, test on an inconspicuous place.

#### STORAGE

Products should be stored in a dry and cool place at a temperature of 5<sup>o</sup>-35<sup>o</sup>C. Protect from humidity and direct sunlight.

#### SHELF LIFE

12 months from the production date in the above mentioned storage conditions. The product should remain in the original unopened packaging bearing the manufacturer's batch number.

#### PACKAGING

Spray 500ml

PACKAGING	CODE	BARCODE
500ml	5200	5204094052005

#### HEALTH AND SAFETY INFORMATION



Skin Corr. 1A: H314 - Causes severe skin burns and eye damage  
P101: If medical advice is needed, have product container or label at hand  
P260: Do not breathe vapours  
P264: Wash thoroughly after handling  
P280: Wear protective gloves/protective clothing/eye protection/face protection  
P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting  
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P390: Absorb spillage to prevent material damage  
P403+P233+P102+P405: Store in a well-ventilated place. Keep container tightly closed. Keep out of reach of children. Store locked up  
P501: Dispose of contents/container according to the separated collection system used in your municipality  
Substances that contribute to the classification: Poly(oxy-1,2-ethanediyl), .alpha.-(carboxymethyl)-.omega.-octyloxy- (8 mol EO average molar ratio) ; Poly(oxy-1,2-ethanediyl), .alpha.-carboxymethyl-.omega.-hexyloxy- (3 mol EO average molar ratio) ; Potassium hydroxide

# Evochem®

EVOCHEM S.A.  
Tzaverdella place 13341, Fyli, Attica, Greece  
Tel.: 210 5590460, 210 5590155 Fax: 210 5590244  
E-mail: info@evochem.gr Website: [www.evochem.gr](http://www.evochem.gr)





## Cleaners

# CL 44 ALUMINIUM CLEANER

Technical Data Sheet

Reviewed: 30.07.2018

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.



# Evochem®

EVOCHEM S.A.  
Tzaverdella place 13341, Fyli, Attica, Greece  
Tel.: 210 5590460, 210 5590155 Fax: 210 5590244  
E-mail: [info@evochem.gr](mailto:info@evochem.gr) Website: [www.evochem.gr](http://www.evochem.gr)

