

# PRODUCT DATA SHEET

## Sika MonoTop<sup>®</sup>-108 WaterPlug

### RAPID SETTING MORTAR

#### DESCRIPTION

Sika MonoTop<sup>®</sup>-108 WaterPlug is a rapid-setting cement mortar for plugging water leaks in concrete and masonry walls.

#### USES

- Instant plugging of negative pressure water inlet through cracks, gravel niches and casting joints
- Instant plugging of drained water outlets, during waterproofing treatments.

#### CHARACTERISTICS / ADVANTAGES

- Rapid setting to avoid washout even in the presence of running water
- Hardens within ~60–80 seconds (at 20 °C)

#### PRODUCT INFORMATION

<b>Chemical base</b>	Rapid-setting cement powder
<b>Packaging</b>	5 kg aluminium bag packed in a cardboard box containing 4 units
<b>Appearance / Colour</b>	Grey powder
<b>Shelf life</b>	15 months
<b>Storage conditions</b>	Store properly in undamaged original sealed packaging, in dry cool conditions.
<b>Density</b>	Bulk density: ~1.1 kg/l

#### APPLICATION INFORMATION

<b>Mixing ratio</b>	1.25–1.40 L of water per 5 kg bag	
<b>Ambient Air Temperature</b>	+5 °C minimum / +30 °C maximum	
<b>Substrate Temperature</b>	+5 °C minimum / +30 °C maximum	
<b>Initial Set Time</b>	<b>Temperature</b>	<b>Initial Set Time</b>
	+5 °C	~120 seconds
	+20 °C	~60 seconds

**Final Set Time****Temperature****Final Set Time**

+5 °C

~210 seconds

+20 °C

~80 seconds

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

The infiltrations (cracks, gravel niches, casting joints, drainage points) shall be widened and deepened by chiselling in order to create a suitable surface to enhance the adhesion.

### MIXING

By hand, rapidly mix mortar and water in a quantity that is adequate to produce a plug to be applied in a few seconds. Protect hands with rubber gloves. The setting time will change by varying the amount of water.

### APPLICATION

Continue to massage the mix for a few seconds until it begins to set, then apply immediately. Press the mortar into the infiltration and maintain adequate pressure for several seconds until the setting has taken effect.

Eliminate excess material by scrapping it away with a spatula after the setting is complete.

### CLEANING OF TOOLS

Removal of fresh remnants from tools and application equipment can be carried out using water immediately after use. Hardened / cured material can only be mechanically removed.

## LIMITATIONS

- After setting, the product can no longer be worked
- Only mix an amount of material which can be applied within a few seconds
- Low temperatures cause setting times to be slightly delayed, high temperatures shorten the setting time
- Use Sika MonoTop®-108 WaterPlug only in presence of water leakages. For concrete repair purposes, use a suitable product from the SikaRep® or Sika MonoTop® range.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control. All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Sika Hellas ABEE**  
**15 Protomagias Str.**  
14568 Kryoneri  
Attica-Greece  
Tel.: +30 210 8160 600  
Fax: +30 210 8160 606  
www.sika.gr | sika@gr.sika.com



SikaMonoTop-108WaterPlug\_en\_GR\_(05-2017)\_1\_1.pdf

Product Data Sheet  
Sika MonoTop®-108 WaterPlug  
May 2017, Version 01.01  
020701010010000284