



#### DESCRIPTION

**MINOS 21 ORIGINAL PENETRATING OIL** is the first Greek multi use spray that marked the introduction of technical sprays in Greece in 1967. Using the old authentic formulation, we link the past with the present emphasizing the timeless value of the product. MINOS 21 is the most useful multi use chemical tool. It has thousands of applications at home, at work, in hobbies etc.

#### ADVANTAGES

- Outstanding mechanical stability
- Prevents wear and sticking
- High viscosity
- Excellent penetration
- Resistant to weather influences
- Resistant to weak acids and bases
- Corrosion prevention
- Water-humidity repellent
- Easy to use

#### APPLICATIONS

**MINOS 21** has thousands of uses around the house, at work, hobbies etc.

- Lubricates moving parts such as hinges, wheels, rollers, chains, and gears.
- Penetrates and releases stuck corroded parts like nuts, bolts, valves and locks.
- Protects against rust and corrosion tools, sporting equipment etc.
- Quickly removes corrosion and grease.
- Displaces moisture to restore water flooded equipment such as engines, plugs and power tools.

#### METHOD OF APPLICATION

1. Before use, shake the can for 2 minutes
2. Apply one layer of MINOS 21 from a distance to the surface to be treated approximately 25 to 30cm
3. Allow product to soak for 5 - 15 minutes and if needed apply a second layer
4. Optimum result is obtained after evaporation of the solvents.
5. After use, turn can upside down and press the nozzle for 5" to clean the valve.

#### CLEANING

With soap and water immediately after use

#### CONSUMPTION

Depends on application

#### TECHNICAL DATA

**Type:** Anticorrosive lubricant

**Form:** Liquid

**Colour:** Transparent – yellow

**Odour:** Characteristic

**Relative density:** 0,88 gr/ml

**Application temperature:** 10°C - 30°C

**VOC (Volatile Organic Compounds) CONTENT:** (Directive 2004/42/CE) EU maximum VOC content limit values for this product (category Be 'Special finishes'): 840 gr/ltr (2010). This product contains maximum 820 gr/ltr VOCs (ready for use product).

#### STORAGE

In a cool and dry place at temperatures between +5°C - +25°C away from sources of ignition. Avoid direct sunlight.

#### SHELF LIFE

At least 5 years in unopened original package, under above mentioned storage conditions.

#### PACKAGING

Spray 400ml

PACKAGING	CODE	BARCODE
400ml	9233	5204094092339

#### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION



Aerosol 1: H229 - Pressurized container: May burst if heated  
Aerosol 1: H222 - Extremely flammable aerosol  
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects  
Eye Irrit. 2: H319 - Causes serious eye irritation  
Repr. 1B: H360D - May damage the unborn child.  
Skin Irrit. 2: H315 - Causes skin irritation  
STOT SE 3: H335 - May cause respiratory irritation  
P101: If medical advice is needed, have product container or label at hand  
P102: Keep out of reach of children  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P211: Do not spray on an open flame or other ignition source  
P251: Do not pierce or burn, even after use  
P280: Wear protective gloves/protective clothing/eye protection/face protection  
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F  
P501: Dispose of contents and / or their container according to the separated collection system used in your municipality  
EUH066: Repeated exposure may cause skin dryness or cracking.  
Substances that contribute to the classification: N-methyl-2-pyrrolidone; Organic modified polydimethylsiloxane ; 1,2,4-trimethylbenzene; Mesitylene  
Restricted to professional users

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.

