

NOVATHINNER PU

Universal solvent

▷ Polyurethane varnishes and paints

▷ Epoxy systems

Description	NOVATHINNER PU is a special solvent suitable for epoxy or polyurethane paints, coatings or varnishes. Also suitable for cleaning surfaces and tools where the above coatings were used.
--------------------	---

Uses	NOVATHINNER PU is suitable for mixing with: <ul style="list-style-type: none">• PLANOFINISH PU 2KS & PLANOFINISH PU 2KS MAT• PLANOFINISH PU 2KS & PLANOFINISH PU 2KS MAT varnishes when applied on natural stones and micro-cement mortars outdoors• The PLANOFINISH PU 2KS varnish when applied on PLANOCOLOR PREMIUM SP for pool protection• Compatible epoxy and polyurethane systems
-------------	---

Technical Data

Product Identity

Form	Liquid
Color	Transparent
Density	0,87 ± 0,05 kg/L

Recommendations	<ul style="list-style-type: none">• Keep away from sources of ignition• To remove paints or varnishes they must still be fresh• Do not mix with PLANOCOLOR PU polyurethane binder• In all cases of mixing check for compatibility• The application is recommended by a professional user
------------------------	--

Consumption	Depending on the type of application.
--------------------	---------------------------------------

Storage NOVATHINNER PU remains stable for at least 12 months from production date, in its sealed original packing, stored in dry conditions and temperatures between +5°C and +35°C.

Packaging Containers of 1L and 5L.

Safety Instructions For further information refer to the Safety Data Sheet of the product.

Warning The technical data and recommendations contained in this leaflet correspond to the best of our knowledge and experience. All the above mentioned information in any case should be considered as merely indicate and subject to confirmation after long term practical applications. In practice, variations in materials, substrates and on-site implementation conditions are such that no warranty can be given on their merchantability or suitability for a particular purpose, and no liability whatsoever from any legal relationship can be claimed against the Company on the basis of any written information, written suggestions tips or other forms of instructions provided. For this reason anyone interested of using the product must be sure beforehand that the product is suitable for the envisaged application. In every case the user alone is fully responsible for any consequences deriving from the use of the product. We retain the right of renewal of the data of the leaflet without warning. For the latest and valid version of the Technical Data Sheet refer to use website www.novamix.gr or directly to the following QR code of the product.



DOMOCHNEMICAL SA
40 PAPANIKOLI STR
CHALANDRI 15232
ATHENS GREECE
T +30 210 68 93 953
F +30 210 68 94 571
novamix@novamix.gr